

2201496

https://www.phoenixcontact.com/us/products/2201496

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Matrix with defined engagement mechanism, for assembly underneath the cover in short design, color: black



## Your advantages

· Easy, tool-free mounting

#### Commercial data

| Item number                          | 2201496             |
|--------------------------------------|---------------------|
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | AC15                |
| Product key                          | ACHEAZ              |
| Catalog page                         | Page 733 (C-1-2013) |
| GTIN                                 | 4046356838641       |
| Weight per piece (including packing) | 3.69 g              |
| Weight per piece (excluding packing) | 3 g                 |
| Customs tariff number                | 85389099            |
| Country of origin                    | DE                  |



https://www.phoenixcontact.com/us/products/2201496



Refer to the data sheet for the range in the download area.

## Technical data

General

#### Notes

| Product properties |                              |                  |
|--------------------|------------------------------|------------------|
|                    | Product type                 | Cover            |
|                    | Housing series               | ME PLC           |
|                    | Туре                         | Cover            |
|                    | Housing type                 | DIN rail housing |
|                    | Ventilation openings present | no               |

#### **Dimensions**

| Width  | 35.27 mm |
|--------|----------|
| Height | 47.37 mm |
| Depth  | 8.7 mm   |

#### Material specifications

| Color (Housing)                        | black (RAL 9005) |
|--|------------------|
| Flammability rating according to UL 94 | V0               |
| CTI according to IEC 60112             | 600              |
| Surface characteristics                | untreated        |
| Housing material                       | Polycarbonate    |

## Environmental and real-life conditions

#### Ambient conditions

| Max. IP code to attain                  | IP20   |
|---|--|
| Ambient temperature (operation)         | -40 °C 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C 70 °C                                   |
| Ambient temperature (assembly)          | -5 °C 100 °C                                   |
| Relative humidity (storage/transport)   | 95 %   |

#### Mounting

| Mounting type | Clip mounting |
|---------------|---------------|
|               |               |

### Packaging specifications

| Type of packaging    | packed in cardboard |
|----------------------|---------------------|
| Outer packaging type | Carton              |



2201496

https://www.phoenixcontact.com/us/products/2201496

## Classifications

#### **ECLASS**

|        | ECLASS-11.0 | 27182702 |
|--------|-------------|----------|
|        | ECLASS-13.0 | 27190605 |
| ETIM   |             |          |
|        |             |          |
|        | ETIM 9.0    | EC001031 |
| UNSPSC |             |          |
|        | UNSPSC 21.0 | 31261500 |



https://www.phoenixcontact.com/us/products/2201496



## Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com