

Filler plugs - ME B-12,5 MKDSO KMGY - 2201862

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail housing, Filler plug for unoccupied terminal points, width: 11 mm, height: 17.05 mm, depth: 8.55 mm, color: light gray (9005)

Figure shows the product in green



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 |
| GTIN |  4 046356 993319 |
| GTIN | 4046356993319 |
| Custom tariff number | 39269097 |

Technical data

Item properties

| | |
|------------------------------|--|
| Brief article description | Filler plugs |
| Type | ME B-12,5 MKDSO KMGY |
| Order No. | 2201862 |
| Housing type | DIN rail housing |
| Range of articles | ME_B_MKDSO |
| Type | Filler plug for unoccupied terminal points |
| Max. IP code to attain | IP20 |
| Mounting type | Latching |
| Ventilation openings present | no |

Dimensions

| | |
|--------------|----------|
| Width [w] | 11 mm |
| Height [h] | 17.05 mm |

Filler plugs - ME B-12,5 MKDSO KMGY - 2201862

Technical data

Dimensions

| | |
|-------------|---------|
| Depth [d] | 8.55 mm |
|-------------|---------|

Material data

| | |
|--|-------------------|
| Housing material | Polyamide |
| Color (RAL) | light gray (9005) |
| Flammability rating according to UL 94 | V0 |

Ambient conditions

| | |
|---|--|
| Ambient temperature (storage/transport) | -40 °C ... 55 °C |
| Ambient temperature (assembly) | -5 °C ... 100 °C |
| Ambient temperature (operation) | -40 °C ... 105 °C (depending on power dissipation) |
| Relative humidity (storage/transport) | 80 % |

Packaging information

| | |
|----------------------------|------|
| Pieces per package | 10 |
| Denomination packing units | Pcs. |

Standards and regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27182702 |
| eCl@ss 11.0 | 27182702 |
| eCl@ss 5.0 | 27141100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27180800 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |

ETIM

| | |
|----------|----------|
| ETIM 6.0 | EC001031 |
| ETIM 7.0 | EC001031 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 31261501 |
|-------------|----------|

Filler plugs - ME B-12,5 MKDSO KMGY - 2201862

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 18.0 | 31261501 |
| UNSPSC 19.0 | 31261501 |
| UNSPSC 20.0 | 31261501 |
| UNSPSC 21.0 | 31261501 |