

UM-ALU 4-72 FRONT 42,5 AP - Front plate



2202086

<https://www.phoenixcontact.com/us/products/2202086>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Press-drawn section housings, Basic profile front plate, width: 71.8 mm, length: 42.5 mm, depth: 2 mm, recommended for UM-ALU 4-..COVER AL lateral elements



Your advantages

- Aluminum extruded profile
- Variety of connection technology
- Can be mounted on the DIN rail
- Available in lengths from 42.5 mm ... 990 mm, can be cut to any length
- Available in overall widths of 75 mm and 105 mm
- EMC protection

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 2202086 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Product key | ACHDFZ |
| GTIN | 4046356987448 |
| Weight per piece (including packing) | 17.8 g |
| Weight per piece (excluding packing) | 17.7 g |
| Country of origin | HU |

UM-ALU 4-72 FRONT 42,5 AP - Front plate



2202086

<https://www.phoenixcontact.com/us/products/2202086>

Technical data

Product properties

| | |
|----------------|------------------------------|
| Product type | Component housing cover |
| Housing series | UM-ALU |
| Product family | UM-ALU 4-72 |
| Type | Basic profile front plate |
| Housing type | Press-drawn section housings |

Dimensions

| | |
|--------|---------|
| Width | 71.8 mm |
| Depth | 2 mm |
| Length | 42.5 mm |

Material specifications

| | |
|-------------------------|----------|
| Color (Housing) | aluminum |
| Surface characteristics | anodized |
| Housing material | Aluminum |

Environmental and real-life conditions

Ambient conditions

| | |
|---|--|
| Max. IP code to attain | IP40 |
| Ambient temperature (operation) | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C |
| Ambient temperature (assembly) | -5 °C ... 100 °C |

Mounting

| | |
|-------------------|--------------------------|
| Mounting position | parallel to the DIN rail |
|-------------------|--------------------------|

Packaging specifications

| | |
|----------------------|---------------------|
| Type of packaging | packed in cardboard |
| Outer packaging type | Carton |

UM-ALU 4-72 FRONT 42,5 AP - Front plate



2202086

<https://www.phoenixcontact.com/us/products/2202086>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27182701 |
| ECLASS-13.0 | 27190605 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002779 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

UM-ALU 4-72 FRONT 42,5 AP - Front plate



2202086

<https://www.phoenixcontact.com/us/products/2202086>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com