

# FLKM 16-PA- 332-5HF/I/MINI-MCR - Front adapter



2318240  
<https://www.phoenixcontact.com/us/products/2318240>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE front adapter, for SIMATIC® S7-300, only in connection with MINI MCR-2-V8-FLK 16. Connectable card: 332-5HF0...-0AB01.

## Commercial data

Item number	2318240
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK2117
Catalog page	Page 507 (C-5-2017)
GTIN	4046356301657
Weight per piece (including packing)	61.2 g
Weight per piece (excluding packing)	61 g
Customs tariff number	85369010
Country of origin	DE

# FLKM 16-PA- 332-5HF/I/MINI-MCR - Front adapter



2318240

<https://www.phoenixcontact.com/us/products/2318240>

## Technical data

### Product properties

Product type	Front adapter
Product family	VARIOFACE

### Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

### Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

### Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Current (per branch)	≤ 50 mA
Current (Voltage supply via screw connection)	≤ 500 mA

### Air clearances and creepage distances

Rated insulation voltage	63 V
Rated surge voltage	0.6 kV (1.2/50 µs)

### Supported controller SIEMENS S7-300 / ET 200 M

Suitable I/O card	6ES7332-5HF0x-0AB0
-------------------	--------------------

### Connection data

#### Connection 1 (control level)

Connection method	Plug-in connection
Number of positions	40

#### Connection 2 (field level)

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	16
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

#### Connection 3 (supply)

Connection method	Screw connection
Number of positions	4
Conductor cross section rigid	0.14 mm² ... 1.5 mm²
Conductor cross section flexible	0.14 mm² ... 1.5 mm²
Conductor cross section AWG	28 ... 16

# FLKM 16-PA- 332-5HF/I/MINI-MCR - Front adapter



2318240

<https://www.phoenixcontact.com/us/products/2318240>

## Dimensions

### Item dimensions

Width	115 mm
Height	21.3 mm
Depth	31.9 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Module)	IP00
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Altitude	≤ 2000 m

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

## Mounting

Mounting type	Plug-in mounting
Mounting position	any

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

# FLKM 16-PA- 332-5HF/I/MINI-MCR - Front adapter



2318240

<https://www.phoenixcontact.com/us/products/2318240>

## Classifications

### ECLASS

ECLASS-11.0	27242292
ECLASS-12.0	27242292
ECLASS-13.0	27242292

### ETIM

ETIM 9.0	EC002584
----------	----------

### UNSPSC

UNSPSC 21.0	32151600
-------------	----------

# FLKM 16-PA- 332-5HF/I/MINI-MCR - Front adapter



2318240  
<https://www.phoenixcontact.com/us/products/2318240>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)