

CABLE-40/2FLK16/ 2,0M/YUC - Front adapter



2321334

<https://www.phoenixcontact.com/us/products/2321334>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cast Yokogawa front adapter with attached round cable and an injection-molded 40-pos. socket strip for the connection of 2 x 8 channels on the field side. Cable length: 2.0 m

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 2321334 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C421 |
| Product key | CK2154 |
| Catalog page | Page 515 (C-5-2019) |
| GTIN | 4046356327411 |
| Weight per piece (including packing) | 367 g |
| Weight per piece (excluding packing) | 366 g |
| Customs tariff number | 85444290 |
| Country of origin | DE |

CABLE-40/2FLK16/ 2,0M/YUC - Front adapter



2321334

<https://www.phoenixcontact.com/us/products/2321334>

Technical data

Product properties

| | |
|--------------|---------------|
| Product type | Front adapter |
|--------------|---------------|

Electrical properties

| | |
|------------------------|-----------------------|
| Operating voltage (DC) | ≤ 30 V DC |
| Nominal operating mode | 100% operating factor |
| Current (Per path) | ≤ 500 mA (uncoiled) |

Supported controller YOKOGAWA CS3000 CentumVP

| | |
|-------------------|--------|
| Suitable I/O card | ADV151 |
| | ADV161 |

Supported controller YOKOGAWA STARDOM

| | |
|-------------------|---------|
| Suitable I/O card | NFAI141 |
| | NFAI143 |

Connection data

Connection 1

| | |
|----------------------------------|--------------------------------|
| Connection in acc. with standard | based on IEC 60603-13 |
| Connection method | Yokogawa, I/O cards compatible |
| Number of connections | 1 |
| Number of positions | 40 |
| Tightening torque | 0.5 Nm (Screw connection) |
| Insertion/withdrawal cycles | > 50 |
| Pitch | 2.54 mm |

Connection 2

| | |
|----------------------------------|-----------------------|
| Connection in acc. with standard | based on IEC 60603-13 |
| Connection method | IDC/FLK socket strip |
| Number of connections | 2 |
| Number of positions | 16 |
| Insertion/withdrawal cycles | > 50 |
| Pitch | 2.54 mm |

Dimensions

Cable

| | |
|--------|-----|
| Length | 2 m |
|--------|-----|

Cable/line

40X0.14 [PVC]

| | |
|---------------------|-----------|
| UL AWM Style | 2464/1061 |
| Number of positions | 40 |

CABLE-40/2FLK16/ 2,0M/YUC - Front adapter



2321334

<https://www.phoenixcontact.com/us/products/2321334>

| | |
|---|---|
| Shielded | yes |
| Cable type | 40X0.14 [PVC] |
| Conductor type | Assembled shielded round cable |
| Conductor structure signal line | 7x 0.16 mm |
| AWG signal line | 26 |
| Conductor cross section | 40x 0.14 mm ² |
| Wire diameter incl. insulation | 1 mm ±0.03 mm |
| External cable diameter | 9.80 mm ±0.3 mm |
| Outer sheath, material | Semi-rigid PVC |
| External sheath, color | gray |
| Conductor material | Tin-plated Cu litz wires |
| Cable resistance | ≤ 145 Ω/km (at 20 °C) |
| Insulation resistance | ≥ 20 MΩ*km (20 °C) |
| Smallest bending radius, fixed installation | 101 mm |
| Smallest bending radius, movable installation | 182 mm |
| Max. bending cycles | 5000 (at a radius of ≥ 18x outside diameter) |
| Halogen-free | no |
| Flame resistance | IEC 60332-1-2 (raw cable) |
| | VDE 0842, Part 332-1-2 (raw cable) |
| | IEC 60332-3-22 (raw cable) |
| | UL VW-1 |
| | CSA FT-1 |
| Resistance to oil | can withstand occasional splashes (raw cable) |

Environmental and real-life conditions

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Degree of protection (Installation location) | ≥ IP54 (Installation location) |
| Ambient temperature (operation) | -40 °C ... 70 °C (fixed installation) |
| | -10 °C ... 70 °C (flexible installation) |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m |

Approvals

UKCA

| | |
|-------------|----------------|
| Certificate | UKCA-compliant |
|-------------|----------------|

Notes

| | |
|---------|--|
| General | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|---------|--|

CABLE-40/2FLK16/ 2,0M/YUC - Front adapter



2321334

<https://www.phoenixcontact.com/us/products/2321334>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27242292 |
| ECLASS-12.0 | 27242292 |
| ECLASS-13.0 | 27242292 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002584 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 32151600 |
|-------------|----------|

CABLE-40/2FLK16/ 2,0M/YUC - Front adapter



2321334

<https://www.phoenixcontact.com/us/products/2321334>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com