

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; controller: MODICON® M340 (BMX DDI 3202K, BMX DDI 6402K, BMX DD0 3202K, BMX DD0 6402K, BMX DDM 3202K); connection 1: Fujitsu connector (1x 40-position); connection 2: IDC/FLK socket strip (4x 14-position); cable length: 1 m

## Your advantages

- Splitting 32 channels into 4 x 8 channels

## Commercial data

Item number	2321729
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C421
Product key	CK2146
Catalog page	Page 491 (C-5-2019)
GTIN	4046356412520
Weight per piece (including packing)	225.4 g
Weight per piece (excluding packing)	220.1 g
Customs tariff number	85444290
Country of origin	DE

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

## Technical data

### Product properties

Product type	System cable
--------------	--------------

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

### Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A (Uncoiled, see derating)
Current (Per path, 70°C)	≤ 0.6 A (Uncoiled, see derating)

#### Supported controller SCHNEIDER ELECTRIC Modicon M340

Suitable I/O card	BMX DDI 3202K
	BMX DDI 6402K
	BMX DD0 3202K
	BMX DD0 6402K
	BMX DDM 3202K

### Cable/line

Cable length	1 m
--------------	-----

#### 10X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	10
Shielded	no
Cable type	10X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	10x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.10 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	98 mm
Max. bending cycles	5000
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Fujitsu40 (B20)	IDC/FLK14-1 (1) = black
Fujitsu40 (A20)	IDC/FLK14-1 (2) = brown
Fujitsu40 (B19)	IDC/FLK14-1 (3) = red
Fujitsu40 (A19)	IDC/FLK14-1 (4) = orange
Fujitsu40 (B18)	IDC/FLK14-1 (5) = yellow
Fujitsu40 (A18)	IDC/FLK14-1 (6) = green
Fujitsu40 (B17)	IDC/FLK14-1 (7) = blue
Fujitsu40 (A17)	IDC/FLK14-1 (8) = violet
Fujitsu40 (B12)	IDC/FLK14-1 (9) = gray
Fujitsu40 (A12)	IDC/FLK14-1 (10) = white
Fujitsu40 (B16)	IDC/FLK14-2 (1) = black
Fujitsu40 (A16)	IDC/FLK14-2 (2) = brown
Fujitsu40 (B15)	IDC/FLK14-2 (3) = red
Fujitsu40 (A15)	IDC/FLK14-2 (4) = orange
Fujitsu40 (B14)	IDC/FLK14-2 (5) = yellow
Fujitsu40 (A14)	IDC/FLK14-2 (6) = green
Fujitsu40 (B13)	IDC/FLK14-2 (7) = blue
Fujitsu40 (A13)	IDC/FLK14-2 (8) = violet
Fujitsu40 (B11)	IDC/FLK14-2 (9) = gray
Fujitsu40 (A11)	IDC/FLK14-2 (10) = white
Fujitsu40 (B10)	IDC/FLK14-3 (1) = black
Fujitsu40 (A10)	IDC/FLK14-3 (2) = brown
Fujitsu40 (B9)	IDC/FLK14-3 (3) = red
Fujitsu40 (A9)	IDC/FLK14-3 (4) = orange
Fujitsu40 (B8)	IDC/FLK14-3 (5) = yellow
Fujitsu40 (A8)	IDC/FLK14-3 (6) = green
Fujitsu40 (B7)	IDC/FLK14-3 (7) = blue
Fujitsu40 (A7)	IDC/FLK14-3 (8) = violet
Fujitsu40 (B2)	IDC/FLK14-3 (9) = gray
Fujitsu40 (A2)	IDC/FLK14-3 (10) = white
Fujitsu40 (B6)	IDC/FLK14-4 (1) = black

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

Fujitsu40 (A6)	IDC/FLK14-4 (2) = brown
Fujitsu40 (B5)	IDC/FLK14-4 (3) = red
Fujitsu40 (A5)	IDC/FLK14-4 (4) = orange
Fujitsu40 (B4)	IDC/FLK14-4 (5) = yellow
Fujitsu40 (A4)	IDC/FLK14-4 (6) = green
Fujitsu40 (B3)	IDC/FLK14-4 (7) = blue
Fujitsu40 (A3)	IDC/FLK14-4 (8) = violet
Fujitsu40 (B1)	IDC/FLK14-4 (9) = gray
Fujitsu40 (A1)	IDC/FLK14-4 (10) = white

## Connection data

### Connection 1

Connection method	Fujitsu connector
Type	FCN 367
Number of connections	1
Number of positions	40
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

### Connection 2

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	4
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

## Classifications

### ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

### ETIM

ETIM 9.0	EC000237
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# CABLE-FCN40/4X14/ 1,0M/M340 - Cable



2321729

<https://www.phoenixcontact.com/us/products/2321729>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)