

2700091

<https://www.phoenixcontact.com/us/products/2700091>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connection element with spring-cage terminal blocks for base mounting

Commercial data

Item number	2700091
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL116
Catalog page	Page 520 (C-6-2019)
GTIN	4046356490146
Weight per piece (including packing)	91.1 g
Weight per piece (excluding packing)	86 g
Customs tariff number	85319000
Country of origin	DE

# PSD-S CE-SM SPRING - Connection element



2700091  
<https://www.phoenixcontact.com/us/products/2700091>

## Technical data

### Product properties

Product type	Assembly element
Scope of delivery	End cover and seal
	End cover and seal
Number of mountable signal elements	max. 5

### Electrical properties

#### General

Nominal input voltage range	12 V AC/DC ... 240 V AC/DC
-----------------------------	----------------------------

### Connection data

#### without ferrule

Connection method	Spring-cage connection
Conductor cross section, flexible	0.5 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	... 15
Stripping length	7 mm


#### With ferrule

Connection method	Spring-cage connection
Conductor cross section, flexible	0.25 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	... 15
Stripping length	7 mm

#### solid

Connection method	Spring-cage connection
Conductor cross section, rigid	0.5 mm² ... 1.5 mm²
Stripping length	7 mm

### Dimensions

Dimensional drawing	
Height	27 mm
Diameter	69 mm

### Material specifications

# PSD-S CE-SM SPRING - Connection element



2700091

<https://www.phoenixcontact.com/us/products/2700091>

Color	black
Material	PA-GF

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65, when installed
Ambient temperature (operation)	-30 °C ... 50 °C

## EMC data

Electromagnetic compatibility	Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC
-------------------------------	---

## Mounting

Mounting type	Base mounting
Assembly instructions	Rubber seal pre-installed for each element
Mounting position	any

# PSD-S CE-SM SPRING - Connection element



2700091

<https://www.phoenixcontact.com/us/products/2700091>

## Classifications

### ECLASS

ECLASS-11.0	27371232
ECLASS-13.0	27371232
ECLASS-12.0	27371232

### ETIM

ETIM 9.0	EC001152
----------	----------

### UNSPSC

UNSPSC 21.0	46171600
-------------	----------

# PSD-S CE-SM SPRING - Connection element



2700091

<https://www.phoenixcontact.com/us/products/2700091>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)