

2700124

https://www.phoenixcontact.com/us/products/2700124

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



LED flashing beacon element, 24 V DC, double flash, yellow

## Your advantages

- · Tool-free element changeover
- · High light and color intensity
- · Can be freely combined
- Minimum LED service life of 50,000 h
- Low power consumption
- · Optimum detection thanks to double flash
- Degree of protection IP65

#### Commercial data

Item number	2700124
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL112
Catalog page	Page 517 (C-6-2019)
GTIN	4046356491181
Weight per piece (including packing)	86 g
Weight per piece (excluding packing)	72 g
Customs tariff number	85318070
Country of origin	DE



2700124

https://www.phoenixcontact.com/us/products/2700124

#### Technical data

#### Product properties

Product type	Optical element
Area of application	Signal tower

#### Electrical properties

Maximum power dissipation for nominal condition	0.84 W
General	
Input voltage	24 V DC
Maximum inrush current	max. 200 mA
Current consumption	35 mA
Source of light type	LED
Operating time	100 %
Service life electrical	max. 50,000 h
Optical signal type	LED flashing beacon with double flash

#### **Dimensions**

Height	65.5 mm
Diameter	70 mm

approx. 1 Hz

#### Material specifications

Signal frequency

Calotte color	yellow
Material	Polycarbonate PC

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP65 (when installed or with end cover)
Ambient temperature (operation)	-20 °C 50 °C

#### EMC data

Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU
---

#### Mounting

Mounting type	Plug-in mounting
Assembly instructions	Rubber seal pre-installed for each element
Mounting position	any



2700124

https://www.phoenixcontact.com/us/products/2700124

## Classifications

UNSPSC 21.0

#### **ECLASS**

ECLASS-11.0	27371220
ECLASS-13.0	27371220
ECLASS-12.0	27371220
ETIM	
ETIM 9.0	EC000232
UNSPSC	

46171600



2700124

https://www.phoenixcontact.com/us/products/2700124

## Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com