2700132

https://www.phoenixcontact.com/us/products/2700132

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

LED flashing light element, 24 V AC/DC, blue



Your advantages

- Tool-free element changeover
- · High light and color intensity
- · Can be freely combined
- Minimum LED service life of 50,000 h
- Low power consumption
- Degree of protection IP65

Commercial data

| Item number | 2700132 |
|--------------------------------------|---------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DR07 |
| Product key | DRL112 |
| Catalog page | Page 516 (C-6-2019) |
| GTIN | 4046356491259 |
| Weight per piece (including packing) | 73.9 g |
| Weight per piece (excluding packing) | 59 g |
| Customs tariff number | 85318070 |
| Country of origin | DE |

PHŒNIX

2700132

https://www.phoenixcontact.com/us/products/2700132



Technical data

Product properties

| Product type | Optical element |
|---|--|
| Area of application | Signal tower |
| Electrical properties | |
| Maximum power dissipation for nominal condition | 0.6 W |
| General | |
| Input voltage | 24 V AC/DC |
| Maximum inrush current | max. 500 mA |
| Current consumption | 25 mA |
| Source of light type | LED |
| Operating time | 100 % |
| Service life electrical | max. 100,000 h |
| Optical signal type | LED flashlight |
| Signal frequency | approx. 1 Hz |
| Dimensions | |
| Height | 65.5 mm |
| Diameter | 70 mm |
| Diameter | |
| Material specifications | |
| Calotte color | blue |
| Material | Polycarbonate PC |
| Environmental and real-life conditions | |
| Degree of protection | IP65 (when installed or with end cover) |
| Ambient temperature (operation) | -20 °C 50 °C |
| EMC data | |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Mounting | |
| Mounting type | Plug-in mounting |
| Assembly instructions | Rubber seal pre-installed for each element |
| Mounting position | any |
| | |



https://www.phoenixcontact.com/us/products/2700132



Classifications

ECLASS

| ECLASS-11.0 | 27371220 |
|-------------|----------|
| ECLASS-13.0 | 27371220 |
| ECLASS-12.0 | 27371220 |

ETIM

| | ETIM 9.0 | EC000232 | | |
|--------|-------------|----------|--|--|
| UNSPSC | | | | |
| | UNSPSC 21.0 | 46171600 | | |

2700132

https://www.phoenixcontact.com/us/products/2700132

Environmental product compliance

China RoHS

Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com