

IB IL PM 3P/N/EF-PAC - Function module



2700965

<https://www.phoenixcontact.com/us/products/2700965>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline power measurement terminal for direct measurement of AC currents up to 5 A, including neutral conductor current and phase conductor voltages up to 400 V AC (phase/neutral conductor) or 690 V AC (phase/phase) complete with accessories (connectors and labeling fields)

Product description

The terminal is designed for use within an Inline station. The power measurement terminal is used to analyze AC power grids. You can use it in distribution systems for measuring current, voltage, and power as well as detecting distortion and harmonics. You can run the power measurement terminal in five operating modes. In "Basic measured values" operating mode, the power measurement terminal is used to acquire mains variables in three-phase mains. Mains variables are phase currents, neutral conductor current, phase and phase-to-phase voltages, active power, reactive power, and apparent power as well as the power factors of phases, energy flow directions, and frequency. The measured variables and operands are calculated in accordance with DIN 40110 Parts 1 and 2 (non-sinusoidal variables). In "Scanning measured values" operating mode, the power measurement terminal acquires the instantaneous values (scanning values) of a measuring signal. This measuring mode is used to analyze the waveform of the measuring signal. In "Heating current measured values" operating mode, the power measurement terminal monitors non-equivalence. Phase currents and phase voltages are measured to detect faults at an early stage. In the "1-phase or 3-phase synchronization" operating modes, the power measurement terminal acquires measured values that can be used for controlling the voltage, speed, and phase angle of a generator so that connection to the mains is possible.

Your advantages

- 4 inputs, 1 A AC ... 5 A AC for phase currents and neutral conductor currents
- 3 inputs for outer conductor voltages up to 690 V AC, supports direct connection
- Triggers for meas. intervals can be freely defined
- Harmonics analysis
- Determination of maximum values
- Operating hours counter
- Energy meter
- Bimetal filtering
- Short-time control

Commercial data

Item number	2700965
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR01
Product key	DRI165
Catalog page	Page 155 (C-6-2019)
GTIN	4046356665919
Weight per piece (including packing)	231.2 g

IB IL PM 3P/N/EF-PAC - Function module



2700965

<https://www.phoenixcontact.com/us/products/2700965>

Weight per piece (excluding packing)	200 g
Customs tariff number	85389099
Country of origin	DE

IB IL PM 3P/N/EF-PAC - Function module




2700965

<https://www.phoenixcontact.com/us/products/2700965>

Technical data

Dimensions

Dimensional drawing	
Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm
Note on dimensions	Housing dimensions

Interfaces

Inline local bus

Number of interfaces	2
Connection method	Inline data jumper
Transmission speed	500 kbps

System properties

Module

ID code (dec.)	220
ID code (hex)	DC
Length code (hex)	0C
Length code (dec)	12
Process data channel	192 bit
Input address area	24 Byte
Output address area	24 Byte
Register length	28 Byte
Required parameter data	29 Byte
Required configuration data	5 Byte

Product properties

Type	modular
Product type	I/O component
Product family	Inline
Operating mode	Process data mode with 12 words, PCP with 2 words

Insulation characteristics

Pollution degree	2 (IEC 60664-1, EN 60664-1)
------------------	-----------------------------

Electrical properties

Maximum power dissipation for nominal condition	0.31 W
Potentials: Communications power (U_L)	
Supply voltage	7.5 V DC (via voltage jumper)
Current draw	typ. 130 mA
Power consumption	typ. 1 W

Connection data

Connection technology	
Connection name	Inline connector

Conductor connection	
Connection method	Spring-cage connection
Conductor cross section rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16
Stripping length	8 mm

Inline connector	
Connection method	Spring-cage connection
Conductor cross section, rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section, flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16
Stripping length	8 mm

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP20
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Standards and regulations

Protection class	II (IEC 61140, EN 61140, VDE 0140-1)
------------------	--------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

IB IL PM 3P/N/EF-PAC - Function module



2700965

<https://www.phoenixcontact.com/us/products/2700965>

Classifications

ECLASS

ECLASS-11.0	27242605
ECLASS-12.0	27242605
ECLASS-13.0	27242605

ETIM

ETIM 9.0	EC001601
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

IB IL PM 3P/N/EF-PAC - Function module



2700965

<https://www.phoenixcontact.com/us/products/2700965>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com