

2701086

https://www.phoenixcontact.com/us/products/2701086

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Runtime license for Visu+ including alarm statistics function where the I/O data and variables in scripting are not limited. 2 direct driver connections are also supported.

Your advantages

- · Access protection with user management
- · Fully scalable process diagrams for using one design on different devices and monitor sizes
- · Multilingual software and projects, thanks to Unicode support and online selection
- · Full SCADA (Supervisory Control And Data Acquisition) function with visualization, trend representation, and alarm management
- · Control coupling with OPC and 2 direct drivers
- Direct driver connection to controllers, e.g., to Siemens S7 or via Modbus/TCP and Modbus/RTU
- · Data logging, trend display, and recipe management
- Scripts can be created in VBA and IL

Commercial data

Item number	2701086
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DR13
Product key	DRDAAB
GTIN	4046356694100
Weight per piece (including packing)	22 g
Weight per piece (excluding packing)	20 g
Customs tariff number	49119900
Country of origin	DE



2701086

https://www.phoenixcontact.com/us/products/2701086

Technical data

duct properties	
Product type	Visualization
stem properties	
Intended use for the software	Visualization
	, recalled to the second secon
icense information	
Type of license	Runtime license
unctionality	
Basic functions	Know-How protection and safety through encoding of projects
	Realtime database coupling with ODBC to MS ACCESS, MS EXCEL and SQL server
	FDA CFR 21 Part 11 compatible
Expanded functionality	Statistical alarm function
Integrated function	Online configuration
	Password protection
	Language selection
	Statistical alarm function
Number of I/O nodes	128000
System requirements	
Hard disk memory	min. 1 GByte (recommended: 2 GB)
RAM	min. 1 GByte (2 GB for Windows Vista and Windows 7)
Supported browsers	Internet Explorer 5.5 or higher
Languages supported	German, English, French, Italian
Optical drive	DVD-ROM
Screen resolution	1024 x 768 pixel(s) (XGA)
System requirements for development environment	
Operating equipment	Keyboard, mouse
Operating system	Windows [®] 11
Operating System	Windows [®] 10
	Windows [®] 8.1
	Windows [®] 8
	Windows [®] 7
	Windows [®] Embedded Standard 7
	Windows [®] Server 2019
	Windows [®] Server 2016
	Windows [®] Server 2012 R2
	Windows [®] Server 2012
	Windows [®] Server 2008 R2
	Windows® Server 2008



2701086

https://www.phoenixcontact.com/us/products/2701086

	Windows [®] Server 2003				
System requirements for runtime environment					
Operating system	Windows [®] 10				
	Windows [®] 8.1				
	Windows [®] 8				
	Windows [®] 7				
	Windows [®] Embedded Standard 7				
	Windows [®] XP Embedded				
	Windows [®] Server 2019				
	Windows [®] Server 2016				
	Windows [®] Server 2012 R2				
	Windows [®] Server 2012				
	Windows [®] Server 2008 R2				
	Windows [®] Server 2008				
	Windows [®] Server 2003				
	Windows [®] CE 5.0				
	Windows [®] CE 6.0				
	Windows [®] Mobile				



2701086

https://www.phoenixcontact.com/us/products/2701086

Classifications

ECLASS

	ECLASS-11.0	27242502		
	ECLASS-12.0	27242502		
	ECLASS-13.0	27242502		
ETIM				
	ETIM 9.0	EC001416		
UNSPSC				
	UNSPSC 21.0	43231500		

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com