

# ANT-OMNI-5900-01 - Antenna



2701347

<https://www.phoenixcontact.com/us/products/2701347>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Omnidirectional antenna for wall or mast mounting, 5 GHz, gain: 5 dBi, degree of protection: IP64, saltwater-resistant, shock- and vibration-resistant, connection: N (female), incl. mounting bracket and mast clamps



## Your advantages

- Ideally suited for stationary 5 GHz applications
- Resistant to salt water

## Commercial data

Item number	2701347
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN23
Product key	DNN2Z1
Catalog page	Page 389 (C-6-2019)
GTIN	4046356739399
Weight per piece (including packing)	270.9 g
Weight per piece (excluding packing)	270 g
Customs tariff number	85177100
Country of origin	PL

## Technical data

### Product properties

Product type	Antenna
Scope of delivery	included mounting bracket and mast clamps
Radiation characteristics	Omnidirectional
Gain	5 dBi
Vertical beamwidth	25 °
Horizontal beamwidth	360 °
Polarization	Linear vertical

### Electrical properties

Frequency band	5 GHz
Frequency range	5.15 GHz ... 5.83 GHz
Impedance	50 Ω
Maximum capacity	6.00 W

### Connection data

#### Connection technology

Connection method	N (female)
Outside diameter	25 mm ... 100 mm (Mast)

### Dimensions

Height	130 mm
Diameter	16 mm

#### External dimensions

Outside diameter	25 mm ... 100 mm (Mast)
------------------	-------------------------

### Material specifications

Material	Fiberglass-reinforced plastic
	V2A
	V2A
Flammability rating according to UL 94	HB

### Cable/line

Connecting cable	No
Other resistance	salt water resistant

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP64
Ambient temperature (operation)	-45 °C ... 70 °C

# ANT-OMNI-5900-01 - Antenna



2701347

<https://www.phoenixcontact.com/us/products/2701347>

Ambient temperature (storage/transport)	-45 °C ... 70 °C
Wind velocity	220 km/h

## Approvals

### Electronic devices in rail vehicles

Shock (operation)	IEC 60721-3-4, 4M5
Vibration (operation)	IEC 60721-3-4, 4M5 Random

## Standards and regulations

Other resistance	salt water resistant
------------------	----------------------

## Mounting

Mounting type	Wall mounting
	Mast mounting
Assembly instructions	Outdoors and indoors

# ANT-OMNI-5900-01 - Antenna



2701347

<https://www.phoenixcontact.com/us/products/2701347>

## Classifications

### ECLASS

ECLASS-11.0	19070105
ECLASS-12.0	19070105
ECLASS-13.0	19070105

### ETIM

ETIM 9.0	EC001698
----------	----------

### UNSPSC

UNSPSC 21.0	43223100
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)