

## Control box - FL RUGGED BOX DIR-1 - 2701440

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Control box set for constructing wireless systems for industrial applications, incl. panel antenna and 3 m antenna cable for 2.4/5 GHz, IP66, with DIN rail, plugs, and screw connections, with 100 ... 240 V power supply unit, without devices



### Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356752206
Weight per Piece (excluding packing)	2,180.000 g
Custom tariff number	85177000
Country of origin	Germany

### Technical data

#### Dimensions

Width	174 mm
Height	254 mm
Depth	137 mm

#### Ambient conditions

Degree of protection	IP66
----------------------	------

Wireless set	Control box (with bore holes incl. sealing plugs, screw connections, and DIN rail), panel antenna incl. antenna cable and 100 ... 240 V AC power supply unit incl. terminal block base
--------------	--

#### General

Housing material	Polycarbonate
------------------	---------------

# Control box - FL RUGGED BOX DIR-1 - 2701440

## Technical data

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Articles in set

### Antenna - ANT-DIR-2459-01 - 2701186



Directional antenna, 2.4 GHz/5 GHz, gain: 9 dBi, polarization: linear, opening angle: h/v 75°/55°, degree of protection: IP67, seawater-resistant, connection: N (female), incl. mounting bracket and mast clips, ATEX and IECEx approval

### Antenna cable - RAD-PIG-RSMA/N-3 - 2903266



Antenna cable, outside diameter: 5 mm (0.2 in.), inner conductor: solid, attenuation: 1.2 / 2.0 / 3.0 dB at 0.9 / 2.4 / 5.8 GHz, connection: N (male) -> RSMA (male), cable length: 3 m (10 ft.)

### Power supply unit - STEP-PS/ 1AC/24DC/0.5 - 2868596



Primary-switched STEP POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/0.5 A

### Feed-through terminal block - PT 2,5-QUATTRO - 3209578



Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, connection method: Push-in connection, number of connections: 4, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, width: 5.2 mm, height: 35.3 mm, color: gray, mounting type: NS 35/7,5, NS 35/15

# Control box - FL RUGGED BOX DIR-1 - 2701440

## Articles in set

### Feed-through terminal block - PT 2,5-QUATTRO BU - 3209581



Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, connection method: Push-in connection, number of connections: 4, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, width: 5.2 mm, height: 35.3 mm, color: blue, mounting type: NS 35/7,5, NS 35/15

### Ground modular terminal block - PT 2,5-QUATTRO-PE - 3209594



Ground modular terminal block, connection method: Push-in connection, number of connections: 4, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, width: 5.2 mm, height: 35.3 mm, color: green-yellow, mounting type: NS 35/7,5, NS 35/15

### RJ45 connector - VS-08-RJ45-5-Q/IP20 - 1656725



RJ45 connector, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: PA, connection method: IDC fast connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet

## Classifications

### eCl@ss

eCl@ss 10.0.1	27180590
eCl@ss 11.0	27180590
eCl@ss 4.0	27240400
eCl@ss 4.1	24010500
eCl@ss 5.0	27144200
eCl@ss 5.1	27144200
eCl@ss 6.0	27144200
eCl@ss 7.0	27144201
eCl@ss 9.0	27180590

### ETIM

ETIM 3.0	EC001423
ETIM 4.0	EC001358

## Control box - FL RUGGED BOX DIR-1 - 2701440

### Classifications

#### ETIM

ETIM 6.0	EC001358
ETIM 7.0	EC001358

#### UNSPSC

UNSPSC 6.01	43172710
UNSPSC 7.0901	43223108
UNSPSC 11	43172710
UNSPSC 12.01	43223108
UNSPSC 13.2	43223108