

AXL F PSDI8/4 1F - Safety module



2701559

<https://www.phoenixcontact.com/us/products/2701559>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Axioline F, Digital input module, Functional safety, PROFIsafe, only for connection to Phoenix Contact or Siemens controller, Digital inputs: 4 (for 2-channel assignment), 8 (for 1-channel assignment), 24 V DC, connection technology: 2-, 3-, 4-conductor, degree of protection: IP20

Product description

The safety module is an input module from the Axioline F product range designed for use in a PROFIsafe system. The module has four safe digital inputs for two-channel assignment or eight safe digital inputs for single-channel assignment. The inputs can be parameterized according to the application and enable sensors to be integrated into the PROFIsafe system.

Your advantages

- Up to Cat. 4/PL e in accordance with EN ISO 13849-1, SIL 3 in accordance with EN IEC 62061, SIL 3 in accordance with IEC 61508

Commercial data

Item number	2701559
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN03
Product key	DNA521
Catalog page	Page 270 (C-6-2019)
GTIN	4046356770026
Weight per piece (including packing)	257 g
Weight per piece (excluding packing)	222 g
Customs tariff number	85389091
Country of origin	DE


AXL F PSDI8/4 1F - Safety module

2701559

<https://www.phoenixcontact.com/us/products/2701559>

Technical data

Dimensions

Dimensional drawing	
Width	53.6 mm
Height	126.1 mm
Depth	54 mm
Note on dimensions	Housing dimensions

Interfaces

Axioline F local bus

Connection method	Bus base module
-------------------	-----------------

System properties

Module

Input address area	5 Byte
Output address area	5 Byte
Required parameter data	22 Byte ((I-and F-parameters))
Required configuration data	10 Byte

Input data

Digital

Input name	Digital inputs
Description of the input	IEC 61131-2 type 3
Number of inputs	4 (for 2-channel assignment) 8 (for 1-channel assignment)
Cable length	max. 1000 m (200 m from the clock output to the safe input (total based on forward and return path))
Connection method	Push-in connection
Connection technology	2-, 3-, 4-conductor
Input voltage	24 V DC (via clock outputs T1 and T2 or external supply)
Input voltage range	-3 V DC ... 30 V DC
Nominal input voltage U_{IN}	24 V DC
Nominal input current at U_{IN}	typ. 4.2 mA
Typical input current per channel	4.2 mA
Input filter time	1.5 ms 3 ms (Default)

AXL F PSDI8/4 1F - Safety module



2701559

<https://www.phoenixcontact.com/us/products/2701559>

	5 ms
	15 ms

Product properties

Type	modular
Product type	I/O component
Product family	Axioline F
Application	Functional safety
	PROFIsafe
	only for connection to Phoenix Contact or Siemens controller

Electrical properties

Maximum power dissipation for nominal condition	24.12 W
Transmission medium	Copper

Potentials

Protective circuit	Protection against polarity reversal, EMC protective circuit, undervoltage detection
--------------------	--

Potentials: Axioline F local bus supply (U_{BUS})

Supply voltage	5 V DC (via bus base module)
Current draw	max. 310 mA
	typ. 280 mA (all inputs set; supply by U_I of 19.2 V DC ... 30 V DC)

Potentials: Supply for digital input modules (U_I)

Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	typ. 9 mA (all inputs set; supply from U_I with 30 V DC; without supply to the sensors via clock supplies T1 and T2)

Connection data

Connection technology

Connection name	Axioline F connector
pluggable	yes

Conductor connection

Connection method	Push-in connection
Conductor cross section rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16

Axioline F connector

Connection method	Push-in connection
Conductor cross section, rigid	0.2 mm ² ... 1.5 mm ²
Conductor cross section, flexible	0.2 mm ² ... 1.5 mm ²
Conductor cross section AWG	24 ... 16

AXL F PSDI8/4 1F - Safety module



2701559

<https://www.phoenixcontact.com/us/products/2701559>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-35 °C ... 60 °C (Mounting position: any)
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 108 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above sea level)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	10 % ... 75 % (on average, 85% infrequently, non-condensing)
Permissible humidity (storage/transport)	10 % ... 75 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

AXL F PSDI8/4 1F - Safety module



2701559

<https://www.phoenixcontact.com/us/products/2701559>

Classifications

ECLASS

ECLASS-11.0	27242604
ECLASS-12.0	27242604
ECLASS-13.0	27242604

ETIM

ETIM 9.0	EC001599
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

AXL F PSDI8/4 1F - Safety module



2701559

<https://www.phoenixcontact.com/us/products/2701559>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com