

Redundancy module - FL RED 2003E PRP - 2701863

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ethernet redundancy module for redundant networks with the redundancy protocol PRP and three RJ45 connections.

Product Description

The compact redundancy modules (RED) enable flexible and economical design of high-availability Ethernet networks in the field of energy and automation. With robustness according to IEC 61850-3 and IEEE 1613, their wide temperature range from -40°C to +70°C, and extensive power supply range from 18 to 58 V DC, they cover all the requirements of industrial and energy technology applications. Parallel redundancy according to IEC 62439 enables high availability networks without switch-over time to be established.

Your advantages

- ✓ Meets the requirements of IEC 61850-3 and IEEE 1613
- ✓ Standardized PRP redundancy function according to IEC 62439-3
- ✓ Easy startup without configuration
- ✓ Parallel redundancy without switch-over times for maximum availability
- ✓ No loss of packets in the event of network failure
- ✓ Low power consumption during operation
- ✓ -40°C ... +70°C ambient temperature
- ✓ Alarm contact



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 867443
GTIN	4046356867443
Weight per Piece (excluding packing)	600.000 g
Custom tariff number	85176200
Country of origin	Germany

Redundancy module - FL RED 2003E PRP - 2701863

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	40 mm
Height	100 mm
Depth	109 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-45 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Air pressure (operation)	70 kPa ... 106 kPa (3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (3000 m above sea level)

Interfaces

Interface	Ethernet (RJ45)
No. of ports	3 (RJ45 ports)
Note on the connection method	Auto negotiation and autocrossing
Transmission physics	Copper
Transmission speed	10/100 Mbps
Transmission length	100 m (per segment)
Data flow control/protocols	IEC 61850-3, IEEE 1613

Function

Basic functions	Ethernet redundancy module for the Parallel Redundancy Protocol
Redundancy	PRP (Parallel Redundancy Protocol)
Status and diagnostic indicators	LEDs: U_{S1} , U_{S2} (redundant voltage supply), link and activity per port

Network expansion parameters

Maximum conductor length (twisted pair)	100 m
---	-------

Supply voltage

Supply voltage	24 V DC (redundant)
	48 V DC (redundant)
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Supply voltage range	18 V DC ... 58 V DC
Typical current consumption	250 mA (at $U_S = 24$ V DC)

Redundancy module - FL RED 2003E PRP - 2701863

Technical data

General

Mounting type	DIN rail
Type AX	Block design
Net weight	417 g

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	16

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 61000-6-4
Noise immunity	IEC 61850-3, IEEE 1613, EN 61000-6-2: 2005

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	19170404
eCl@ss 11.0	19170404
eCl@ss 4.0	24010500
eCl@ss 4.1	24010500
eCl@ss 5.0	19030100
eCl@ss 5.1	19030100
eCl@ss 6.0	19170100
eCl@ss 7.0	19170101
eCl@ss 9.0	19170101

ETIM

ETIM 4.0	EC001478
ETIM 6.0	EC000515

Redundancy module - FL RED 2003E PRP - 2701863

Classifications

ETIM

ETIM 7.0	EC000515
----------	----------

UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	43201404
UNSPSC 18.0	43201404
UNSPSC 19.0	43201404
UNSPSC 20.0	43201404
UNSPSC 21.0	43201404

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
-----------	--	---	---------------

cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
------------	--	---	---------------

cULus Listed			
--------------	--	--	--

