


# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Motor terminal block, four-level, cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 24 - 12, connection method: screw connection, width: 6.2 mm, color: gray, mounting type: NS 35/7,5, NS 35/15

## Your advantages

- It is used for programmable or self-monitoring initiators which are additionally controlled via the second feed-through level
- This terminal block has 2 feed-through levels and 2 busbar levels

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2718206             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE12                |
| Product key                          | BE1218              |
| Catalog page                         | Page 487 (C-1-2019) |
| GTIN                                 | 4017918062279       |
| Weight per piece (including packing) | 27.155 g            |
| Weight per piece (excluding packing) | 27.15 g             |
| Customs tariff number                | 85369010            |
| Country of origin                    | PL                  |

# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

## Technical data

### Product properties

|                       |                      |
|-----------------------|----------------------|
| Product type          | Motor terminal block |
| Number of connections | 7                    |
| Number of rows        | 4                    |
| Potentials            | 4                    |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|   |        |
|---|--------|
| Rated surge voltage                             | 6 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                 |                     |
|---------------------------------|---------------------|
| Grounding foot                  | Yes                 |
| Number of connections per level | 2                   |
| Nominal cross section           | 2.5 mm <sup>2</sup> |

### 2nd, 3rd and 4th level

|   |   |
|---|---|
| Screw thread  | M3  |
| Note  | Please observe the current carrying capacity of the DIN rails.                    |
| Tightening torque   | 0.5 ... 0.6 Nm  |
| Stripping length  | 8 mm  |
| Internal cylindrical gage   | A3  |
| Connection in acc. with standard                                  | IEC 60947-7-1/IEC 60947-7-2   |
| Conductor cross section rigid                                     | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Cross section AWG   | 24 ... 12 (converted acc. to IEC)   |
| Conductor cross section flexible                                  | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                       |
| Conductor cross section, flexible [AWG]                           | 24 ... 14 (converted acc. to IEC)   |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                      |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                      |
| Cross-section with insertion bridge, rigid                        | 4 mm <sup>2</sup>   |
| Cross-section with insertion bridge, flexible                     | 2.5 mm <sup>2</sup>   |
| Nominal current   | 24 A  |
| Maximum load current  | 26 A (with a 2.5 mm <sup>2</sup> conductor cross section)                         |
| Nominal voltage   | 400 V (when using EB insertion bridges, the nominal voltage is reduced to 250 V.) |
| Nominal cross section   | 2.5 mm <sup>2</sup>   |

### Dimensions

|        |         |
|--------|---------|
| Width  | 6.2 mm  |
| Height | 82.5 mm |

# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

|                    |         |
|--------------------|---------|
| Depth on NS 35/7,5 | 70 mm   |
| Depth on NS 35/15  | 77.5 mm |

## Material specifications

|   |        |
|---|--------|
| Color   | gray   |
| Flammability rating according to UL 94                                  | V2     |
| Insulating material group   | I      |
| Insulating material   | PA     |
| Static insulating material application in cold                          | -40 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B)        | 125 °C |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV      |
| Result                | Test passed |

### Temperature-rise test

|  |                                     |
|--|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq$ 45 K |
| Result   | Test passed                         |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Short-time withstand current 4 mm <sup>2</sup>   | 0.48 kA                             |
| Result   | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                |        |
|----------------|--------|
| Rotation speed | 10 rpm |
| Revolutions    | 135    |

# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

|                                |                              |
|--------------------------------|------------------------------|
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|  |  |
|--|--|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)  |
| Ambient temperature (assembly)           | -5 °C ... 70 °C  |
| Ambient temperature (actuation)          | -5 °C ... 70 °C  |
| Permissible humidity (operation)         | 20 % ... 90 %  |
| Permissible humidity (storage/transport) | 30 % ... 70 %  |

## Standards and regulations

|                                  |                             |
|----------------------------------|-----------------------------|
| Connection in acc. with standard | IEC 60947-7-1/IEC 60947-7-2 |
|----------------------------------|-----------------------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141128 |
| ECLASS-12.0 | 27141128 |
| ECLASS-13.0 | 27250112 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000900 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# VIOK 1,5-3D/PE - Motor connection terminal block



2718206

<https://www.phoenixcontact.com/us/products/2718206>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)