

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Electronic circuit breaker, 1-pos., active current limitation, status output and reset input, plug for base element.

Your advantages

- Individually adjustable with protective plugs
- Protective plug with fixed nominal current value as protection against unintentional changes
- Active current limitation to improve the capacity of the upstream power supply
- Remote reconnection with the reset function
- Increased system transparency with integrated remote message function

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 2800909 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL04 |
| Product key | CLA134 |
| Catalog page | Page 383 (C-4-2019) |
| GTIN | 4046356690867 |
| Weight per piece (including packing) | 34.67 g |
| Weight per piece (excluding packing) | 34.6 g |
| Customs tariff number | 85362010 |
| Country of origin | DE |

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

Technical data

Notes

| | |
|---------|--|
| General | When mounted in rows without convection cooling, the nominal device current should only be led to a maximum of 80% due to the thermal effect during continuous operation (100% operating factor). Special precautionary measures must be taken in systems or machines, to prevent components from restarting (e.g., use of a safety PLC). Parallel connection of multiple circuit breakers is not permitted. |
|---------|--|

Product properties

| | |
|---------------------|-------------------------|
| Type | Male |
| Product type | Device circuit breakers |
| Product family | CB E |
| Number of positions | 1 |
| No. of channels | 1 |

Insulation characteristics

| | |
|---------------------|---|
| Degree of pollution | 2 |
|---------------------|---|

Electrical properties

General

| | |
|------------------------------|---|
| Operating voltage | 24 V DC |
| | 18 V DC ... 30 V DC |
| Nominal current I_N | 2 A |
| Rated surge voltage | 0.5 kV |
| Tripping method | E (electronic) |
| Required backup fuse | not required, integrated failsafe element |
| Dielectric strength | max. 30 V DC (Load circuit) |
| Active current limitation | typ. $1.25 \times I_N$ |
| Fuse | electronic |
| Closed circuit current I_0 | typ. 8 mA (When switched on) |
| | typ. 11 mA (With status output) |
| Power dissipation | 0.46 W (Nominal operation) |
| Temperature derating | 2 A (at 50 °C) |
| MTBF (IEC 61709, SN 29500) | 8320000 h (at 25 °C with 80 % load) |
| | 7410000 h (at 40 °C with 80 % load) |
| Voltage drop | 100 mV (at I_N) |
| Fail-safe element | 4 A DC |

Load circuit

| | |
|-------------------------|--|
| Shutdown time | 400 ms (see time/current characteristic curve) |
| Undervoltage switch-off | < 14 V (typ. OFF) |
| | > 17 V (typ. ON) |

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

| | |
|----------------------|----------|
| Max. capacitive load | 20000 µF |
|----------------------|----------|

Auxiliary contact

| | |
|-------------------------|----------------------------------|
| Contact connection type | Positive-switching signal output |
|-------------------------|----------------------------------|

Reset

| | |
|---------------------|---|
| Input voltage range | 7 V DC ... 30 V DC (Reset with falling edge) |
| Current consumption | typ. 2.6 mA (at 24 V DC) |
| Pulse length | min. 20 ms |
| Voltage | < 3 V DC (Low state) > 8 V DC (High state) |


Status output

| | |
|----------------|----------------------------------|
| Output voltage | 24 V DC |
| Output current | max. 0.2 A (Short-circuit-proof) |

Connection data

| | |
|-------------------|-----------|
| Connection method | pluggable |
|-------------------|-----------|

Dimensions

| | |
|------------------------|--|
| Dimensional drawing |  |
| Width | 12.3 mm |
| Height | 45 mm |
| Depth | 52 mm |
| Complete module width | 12.3 mm |
| Complete module height | 90 mm |
| Complete module depth | 77.3 mm |

Material specifications

| | |
|--|-------------------------------------|
| Color | gray (RAL 7042) black (RAL 9005) |
| Flammability rating according to UL 94 | V-0 |

Environmental and real-life conditions

Ambient conditions

| | |
|---|--|
| Degree of protection | IP30 (Actuation area) |
| Ambient temperature (operation) | -25 °C ... 50 °C (non-condensing) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Humidity test | 96 h, 95 % RH, 40 °C |
| Vibration (operation) | 3g (according to IEC 60068-2-6, Test Fc) |

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

Approvals

UL approval

| | |
|----------------|-----------------------|
| Identification | UL Listed UL 508 |
| | UL Recognized UL 2367 |

Shipbuilding approval

| | |
|----------------|--------|
| Identification | DNV GL |
|----------------|--------|

Standards and regulations

| | |
|--------------------------|-----------------------|
| Standard designation | EMV |
| Standards/specifications | EN 61000-6-3 |
| Note | Interference emission |
| Standard designation | EMV |
| Standards/specifications | EN 61000-6-2 |
| Note | Noise immunity |

Mounting

| | |
|---------------|-----------------|
| Mounting type | on base element |
|---------------|-----------------|

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27140401 |
| ECLASS-12.0 | 27140401 |
| ECLASS-13.0 | 27140401 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003538 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

CB E1 24DC/2A S-R P - Electronic circuit breaker



2800909

<https://www.phoenixcontact.com/us/products/2800909>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 25; |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com