

2802578

https://www.phoenixcontact.com/us/products/2802578

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Component connector, pitch: 6 mm, number of positions: 1, color: gray, mounting type: Plug-in mounting

## Your advantages

· Is supplied as a set with two plug sockets

#### Commercial data

| Item number                          | 2802578                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 10 pc                          |
| Minimum order quantity               | 10 pc                          |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BE19                           |
| Product key                          | BE1Z3X                         |
| Catalog page                         | Page 510 (C-1-2019)            |
| GTIN                                 | 4017918074494                  |
| Weight per piece (including packing) | 7.85 g                         |
| Weight per piece (excluding packing) | 4.8 g                          |
| Customs tariff number                | 85366990                       |
| Country of origin                    | PL                             |



2802578

https://www.phoenixcontact.com/us/products/2802578

## Technical data

#### Product properties

| Product type        | Component plug terminal block |
|---------------------|-------------------------------|
| Number of positions | 1                             |
| Pitch               | 6 mm                          |

#### Connection data

| Tightening torque | 0.5 0.6 Nm |
|-------------------|------------|
| Tightening torque | 0.5 0.6 Nm |

#### **Dimensions**

| Pitch | 6 mm |
|-------|------|
| FILCH | 6 mm |

## Material specifications

| Color                                  | gray |
|--|------|
| Flammability rating according to UL 94 | V2   |
| Insulating material                    | PA   |

#### Environmental and real-life conditions

#### Ambient conditions

| Ambient temperature (operation)          | -60 °C 105 °C (max. short-term operating temperature RTI Elec.)       |
|--|---|
| Ambient temperature (storage/transport)  | -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C 70 °C   |
| Ambient temperature (actuation)          | -5 °C 70 °C   |
| Permissible humidity (storage/transport) | 30 % 70 %   |

#### Mounting

| Mounting type | Plug-in mounting |
|---------------|------------------|
|---------------|------------------|



2802578

https://www.phoenixcontact.com/us/products/2802578

## Classifications

UNSPSC 21.0

#### **ECLASS**

| ECLASS-11.0 | 27141149 |
|-------------|----------|
| ECLASS-12.0 | 27141149 |
| ECLASS-13.0 | 27250305 |
| ETIM        |          |
| ETIM 9.0    | EC002018 |
| UNSPSC      |          |

39121600



https://www.phoenixcontact.com/us/products/2802578



## Environmental product compliance

| China RoHS | Environmentally Friendly Use Period = 50 years   |
|------------|--|
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com