

FL CAT5 PATCH 1,0 - Patch cable



2832276

<https://www.phoenixcontact.com/us/products/2832276>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Patch cable, CAT5, assembled, 1 m



Commercial data

Item number	2832276
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB11
Product key	ABNABG
Catalog page	Page 513 (C-2-2019)
GTIN	4046356044004
Weight per piece (including packing)	48.8 g
Weight per piece (excluding packing)	47.9 g
Customs tariff number	85444210
Country of origin	PL

FL CAT5 PATCH 1,0 - Patch cable



2832276

<https://www.phoenixcontact.com/us/products/2832276>

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45
Shielded	yes

Insulation characteristics

Overvoltage category	I
Degree of pollution	1

Electrical properties

Rated voltage (III/2)	150 V
Contact resistance	$\leq 0.003 \Omega$ (IEC 60603-7)
Nominal voltage U_N	150 V _{rms}
Nominal current I_N	1.5 A
Transmission speed	1 Gbps
Wave impedance	100 Ω

Mechanical properties

Mechanical data

Insertion force per signal contact	30.00 N
Extraction force per signal contact	50 N

Material specifications

Flammability rating according to UL 94	V0
Outer sheath, material	LSFROH
Conductor material	Bare Cu litz wires

Dimensions

Width	12.6 mm
Height	6.6 mm
Length	40.05 mm

External dimensions

External diameter max.	6.2 mm
------------------------	--------

Connector

Connection 1

Type	Plug straight RJ45
Shielded	yes
Insertion/withdrawal cycles	≥ 750

FL CAT5 PATCH 1,0 - Patch cable



2832276

<https://www.phoenixcontact.com/us/products/2832276>

Degree of protection	IP20
----------------------	------

Connection 2

Type	Plug straight RJ45
------	--------------------

Cable/line

Cable length	1.00 m
External cable diameter	5.50 mm
Outer sheath, material	LSFROH
Single wire, number of litz wires	8
Single wire, material	Cu litz wire
Single wire, cross section	0.14 mm ²
Cable cross section	0.14 mm ²
Conductor material	Bare Cu litz wires
Twisted pairs	yes
Type of pair shielding	none
Overall twist	Twisted pairs
Shielding	SF/UTP
Test voltage Core/Core	1 kV DC (1 min.)
Test voltage Core/Shield	1.00 kV DC (1 min.)
Test voltage, cable	1 kV DC (1 min.)
Wave impedance	100 Ω
Smallest bending radius, fixed installation	30 mm
Concentration of fumes	in accordance with IEC 61034
Flame resistance	according to IEC 60332-3C

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-10 °C ... 60 °C

Standards and regulations

Flame resistance	according to IEC 60332-3C
Concentration of fumes	in accordance with IEC 61034

FL CAT5 PATCH 1,0 - Patch cable

2832276

<https://www.phoenixcontact.com/us/products/2832276>



Classifications

ECLASS

ECLASS-11.0	27060308
ECLASS-12.0	27060308
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC002599
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

FL CAT5 PATCH 1,0 - Patch cable



2832276

<https://www.phoenixcontact.com/us/products/2832276>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com