

FL CAT5 PATCH 5,0 - Patch cable



2832580

<https://www.phoenixcontact.com/us/products/2832580>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Patch cable, CAT5, assembled, 5 m



Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 2832580 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB11 |
| Product key | ABNABG |
| Catalog page | Page 721 (C-2-2019) |
| GTIN | 4046356044080 |
| Weight per piece (including packing) | 181 g |
| Weight per piece (excluding packing) | 22.22 g |
| Customs tariff number | 85444210 |
| Country of origin | PL |

FL CAT5 PATCH 5,0 - Patch cable



2832580

<https://www.phoenixcontact.com/us/products/2832580>

Technical data

Product properties

| | |
|---------------------|-------------------------|
| Product type | Data cable preassembled |
| Sensor type | Ethernet |
| Number of positions | 8 |
| Connection profile | RJ45 |

Electrical properties

| | |
|-----------------------|-----------------------------------|
| Contact resistance | $\leq 0.003 \Omega$ (IEC 60603-7) |
| Nominal voltage U_N | 150 V _{rms} |
| Nominal current I_N | 1.5 A |
| Transmission speed | 1 Gbps |

Mechanical properties

Mechanical data

| | |
|-------------------------------------|---------|
| Insertion force per signal contact | 30.00 N |
| Extraction force per signal contact | 50 N |

Material specifications

| | |
|--|--------|
| Flammability rating according to UL 94 | V0 |
| Outer sheath, material | LSFROH |

Dimensions

| | |
|--------|----------|
| Width | 12.6 mm |
| Height | 6.6 mm |
| Length | 40.05 mm |

External dimensions

| | |
|------------------------|--------|
| External diameter max. | 6.2 mm |
|------------------------|--------|

Connector

Connection 1

| | |
|-----------------------------|--------------------|
| Type | Plug straight RJ45 |
| Shielded | yes |
| Insertion/withdrawal cycles | ≥ 750 |
| Degree of protection | IP20 |

Connection 2

| | |
|------|--------------------|
| Type | Plug straight RJ45 |
|------|--------------------|

Cable/line

| | |
|-------------------------|---------|
| Cable length | 5.00 m |
| External cable diameter | 5.50 mm |

FL CAT5 PATCH 5,0 - Patch cable



2832580

<https://www.phoenixcontact.com/us/products/2832580>

| | |
|---|------------------------------|
| Outer sheath, material | LSFROH |
| Single wire, number of litz wires | 8 |
| Single wire, material | Cu litz wire |
| Single wire, cross section | 0.14 mm ² |
| Shielding | SF/UTP |
| Smallest bending radius, fixed installation | 30 mm |
| Halogen-free | according to IEC 60754-1 |
| Concentration of fumes | in accordance with IEC 61034 |
| Flame resistance | according to IEC 60332-3C |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -10 °C ... 60 °C |

Standards and regulations

| | |
|------------------------|------------------------------|
| Flame resistance | according to IEC 60332-3C |
| Concentration of fumes | in accordance with IEC 61034 |

FL CAT5 PATCH 5,0 - Patch cable



2832580

<https://www.phoenixcontact.com/us/products/2832580>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27060308 |
| ECLASS-12.0 | 27060308 |
| ECLASS-13.0 | 27060307 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002599 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

FL CAT5 PATCH 5,0 - Patch cable



2832580

<https://www.phoenixcontact.com/us/products/2832580>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com