


Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ethernet Switch, 8 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function

Your advantages

- ✓ Auto negotiation and autocrossing detection simplifies installation and setup
- ✓ Local diagnostic indicators with LEDs
- ✓ Security options with cable locking
- ✓ Relay contact for alarm processing of voltage states
- ✓ RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 952204 |
| GTIN | 4017918952204 |
| Weight per Piece (excluding packing) | 439.300 g |
| Custom tariff number | 85176200 |
| Country of origin | Taiwan |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|-------|--------|
| Width | 135 mm |
|-------|--------|

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Technical data

Dimensions

| | |
|--------|---------|
| Height | 94.3 mm |
| Depth | 30 mm |

Ambient conditions

| | |
|--|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | 0 °C ... 55 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 86 kPa ... 108 kPa (up to 1500 m above sea level) |
| Air pressure (storage/transport) | 66 kPa ... 108 kPa (up to 3500 m above sea level) |

Interfaces

| | |
|-------------------------------|---------------------------------------|
| Interface | Ethernet (RJ45) |
| No. of ports | 8 (RJ45 ports) |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 Mbps |
| Transmission length | 100 m (per segment) |
| Signal LEDs | Data receive, link status |
| Interface | Potential-free signaling contact |
| Connection method | Plug-in/screw connection via COMBICON |

Function

| | |
|----------------------------------|---|
| Basic functions | Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode |
| Additional functions | Autonegotiation |
| Status and diagnostic indicators | LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port |
| Signal contact control voltage | 24 V DC (typical) |

Network expansion parameters

| | |
|---|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC (redundant) |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 18.5 V DC ... 30.2 V DC |
| Typical current consumption | 200 mA (at U _S = 24 V DC) |
| | 95 mA (at U _S = 24 V DC: >VC 14) |

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Technical data

General

| | |
|------------------|---|
| Mounting type | DIN rail |
| Type AX | Block design |
| Net weight | 417 g |
| Housing material | Aluminum |
| MTTF | 45.9 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%) |

Standards and Regulations

| | |
|---|---|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Type of test | Shock in acc. with EN 60068-2-27/IEC 60068-2-27 |
| Test result | Operation: 25g, 11 ms duration, semi-sinusoidal shock impulse |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2:2005 |
| Vibration (storage/transport) | 5g, 150 Hz, in acc. with IEC 60068-2-6 |
| Free from substances that could impair the application of coating | In acc. with VW specification |
| Vibration (operation) | in acc. with IEC 60068-2-6: 5g, 150 Hz |
| UL, USA/Canada | Class I, Div. 2, Groups A, B, C, D, T4 |
| | UL 508 Listed |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 10; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 19170402 |
| eCl@ss 11.0 | 19170402 |
| eCl@ss 4.0 | 27250500 |
| eCl@ss 4.1 | 27250500 |
| eCl@ss 5.0 | 19030100 |
| eCl@ss 5.1 | 19030100 |
| eCl@ss 6.0 | 19170100 |
| eCl@ss 7.0 | 19170106 |
| eCl@ss 9.0 | 19170106 |

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 6.0 | EC000734 |
| ETIM 7.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43222612 |
| UNSPSC 19.0 | 43222612 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / KC / EAC / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approval details

| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|-----------|--|---|---------------|

| | | | |
|------------|--|---|---------------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|------------|--|---|---------------|


| | | |
|-----|--|---------------------|
| EAC | | RU*-DE.*.B.00741/19 |
|-----|--|---------------------|

Industrial Ethernet Switch - FL SWITCH SF 8TX - 2832771

Approvals

| | | | |
|----|---|---|--------------------------|
| KC |  | http://eng.kcc.go.kr/user/ehpMain.do | KCC-REI- PCK- FL28327 |
|----|---|---|--------------------------|

| | | | |
|-----|---|--|---------------------|
| EAC |  | | RU*-DE.*.B.00741/19 |
|-----|---|--|---------------------|

| | | | |
|--------------|---|--|--|
| cULus Listed |  | | |
|--------------|---|--|--|