

# MINI-BAT/12DC/1.6AH - Battery module



2866572

<https://www.phoenixcontact.com/us/products/2866572>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Energy storage device, lead AGM, VRLA technology, 12 V DC, 1.6 Ah.

## Product description

MINI-BAT - energy storage with lead AGM technology for maximum buffer times.

## Your advantages

- Maximum buffer times

## Commercial data

Item number	2866572
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CM24
Product key	CMUEV3
Catalog page	Page 353 (C-4-2019)
GTIN	4046356476492
Weight per piece (including packing)	829.5 g
Weight per piece (excluding packing)	800 g
Customs tariff number	85072080
Country of origin	CN

# MINI-BAT/12DC/1.6AH - Battery module



2866572

<https://www.phoenixcontact.com/us/products/2866572>

## Technical data

### Input data

Input voltage	12 V DC
Buffer period	60 min. (1 A)
	6 min. (4 A)

### Output data

Nominal output voltage	12 V DC
Output current $I_{\max}$	10 A
Output fuse	10 A
Connection in parallel	5
Connection in series	No

### Battery operation

Nominal output voltage	12 V DC
Nominal output current ( $I_N$ )	10 A

### Energy storage

End-of-charge voltage	13.8 V
Charging current	1 A
Nominal capacity	1.6 Ah
Battery module service life	3 Years (20 °C)
Latest startup (battery only) - range	3 Months (0 °C ... 20 °C)
	3 Months ... 1 Months (20 °C ... 30 °C)
	1 Months (30 °C ... 40 °C)
Battery technology	VRLA-AGM
Memory medium	Lead rechargeable battery module
Accumulator type	YUASA NP0.8-12
	YUCEL Y0.8-12
	YUVOLT 0.8-12
Number of cells	1
Size designation	Block
Battery pack	yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
IQ technology	no
Suitable for fast charging	yes

### Product properties

Product type	Battery unit
Product family	Battery module
Application	for MINI DC-UPS
Disposal	Used batteries must not be thrown away with household waste,

# MINI-BAT/12DC/1.6AH - Battery module



2866572

<https://www.phoenixcontact.com/us/products/2866572>

	they should instead be disposed of in accordance with applicable national regulations.
IQ technology	no

## Insulation characteristics

Protection class	III
------------------	-----

## Dimensions

Width	67.5 mm
Height	99 mm
Depth	107 mm

## Installation dimensions

Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	30 mm / 30 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C
Max. permissible relative humidity (operation)	95 %

## Ex data

Suited for EX-applications	No
----------------------------	----

# MINI-BAT/12DC/1.6AH - Battery module



2866572

<https://www.phoenixcontact.com/us/products/2866572>

## Classifications

### ECLASS

ECLASS-11.0	27050403
ECLASS-13.0	27050403
ECLASS-12.0	27050403

### ETIM

ETIM 9.0	EC000357
----------	----------

### UNSPSC

UNSPSC 21.0	26111700
-------------	----------

# MINI-BAT/12DC/1.6AH - Battery module



2866572

<https://www.phoenixcontact.com/us/products/2866572>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 3
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)