RAD-ISM-900-ANT-YAGI-3-N - Antenna

2867801

https://www.phoenixcontact.com/us/products/2867801

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Directional antenna, 868 MHz / 900 MHz, gain: 5 dBi, polarization: linear, opening angle: h/v 168°/78°, degree of protection: IP65, connection: N (female), incl. mounting bracket and mast clips

Your advantages

- · For stationary or linear mobile applications
- · For point-to-point connections
- · For large distances

Commercial data

| Item number | 2867801 |
|--------------------------------------|---------------------|
| Packing unit | 1 pc |
| Sales key | DN23 |
| Product key | DNC6A3 |
| Catalog page | Page 395 (C-6-2019) |
| GTIN | 4017918976668 |
| Weight per piece (including packing) | 1,277.8 g |
| Weight per piece (excluding packing) | 1,205 g |
| Customs tariff number | 85177100 |
| Country of origin | US |

RAD-ISM-900-ANT-YAGI-3-N - Antenna



https://www.phoenixcontact.com/us/products/2867801



Technical data

Product properties

| Product type | Antenna |
|----------------------|-------------------------------|
| Gain | 5 dBi |
| Vertical beamwidth | 78 ° |
| Horizontal beamwidth | 168 ° |
| Polarization | Linear vertical or horizontal |

Electrical properties

| Frequency band | 900 MHz |
|-----------------|---------|
| Frequency range | 900 MHz |
| Impedance | 50 Ω |

Connection data

| Connection technology | | |
|-----------------------|-------------------|-------------------------------|
| | Connection method | N (female) with cable (0.6 m) |
| | Outside diameter | 32 mm 60 mm (Mast) |

Dimensions

| Width | 6 cm |
|---------------------|-------|
| Height | 17 cm |
| External dimensions | |

| Outside diameter | 32 mm 60 mm (Mast) |
|------------------|--------------------|
|------------------|--------------------|

Material specifications

| Material | Aluminum |
|----------|----------|
| | V2A |
| | V2A |

Cable/line

| Cable length | 0.60 m |
|------------------|--------|
| Connecting cable | yes |

Environmental and real-life conditions

| Ambient conditions | |
|---------------------------------|--------------|
| Degree of protection | IP65 |
| Ambient temperature (operation) | -40 °C 80 °C |
| Wind velocity | 15.4321 km/h |

Mounting

| Mounting type | Mast mounting |
|---------------|---------------|
|---------------|---------------|

RAD-ISM-900-ANT-YAGI-3-N - Antenna



https://www.phoenixcontact.com/us/products/2867801



Classifications

ECLASS

| ECLASS-11.0 | 19070105 |
|-------------|----------|
| ECLASS-12.0 | 19070105 |
| ECLASS-13.0 | 19070105 |

ETIM

| | ETIM 9.0 | EC001698 |
|----|-------------|----------|
| UN | ISPSC | |
| | UNSPSC 21.0 | 43223100 |



2867801

https://www.phoenixcontact.com/us/products/2867801



Environmental product compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|---|
| | |
| | |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com