

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Primary-switched STEP POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/4.2 A

## Product description

STEP POWER power supplies for distribution boards

The STEP POWER power supply range was developed especially for building automation. The low idling losses and high degree of efficiency ensure maximum energy efficiency. They allow flexible use and can be snapped onto the DIN rail or screwed onto an even surface.

## Your advantages

- Flexible mounting by simply snapping onto the DIN rail or screwing onto a level surface
- Reliable power supply thanks to high MTBF (mean time between failures) of more than 500,000 hours and U/I characteristic curve
- Energy savings thanks to maximum energy efficiency and incredibly low idling losses

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2868664             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | CM13                |
| Product key                          | CMPS13              |
| Catalog page                         | Page 281 (C-4-2019) |
| GTIN                                 | 4046356287975       |
| Weight per piece (including packing) | 380.8 g             |
| Weight per piece (excluding packing) | 330 g               |
| Customs tariff number                | 85044095            |
| Country of origin                    | VN                  |

## Technical data

### Input data

#### AC operation

|  |   |
|--|---|
| Nominal input voltage range              | 100 V AC ... 240 V AC                           |
| Input voltage range                      | 85 V AC ... 264 V AC<br>95 V DC ... 250 V DC    |
| Input voltage range AC                   | 85 V AC ... 264 V AC                            |
| Input voltage range DC                   | 95 V DC ... 250 V DC                            |
| Voltage type of supply voltage           | AC/DC   |
| Inrush current                           | < 15 A (typical)                                |
| Inrush current integral ( $I^2t$ )       | < 1 A <sup>2</sup> s                            |
| AC frequency range                       | 45 Hz ... 65 Hz                                 |
| Frequency range DC                       | 0 Hz  |
| Mains buffering time                     | typ. 20 ms (120 V AC)<br>typ. 100 ms (230 V AC) |
| Current consumption                      | 1.3 A (120 V AC)<br>0.8 A (230 V AC)            |
| Nominal power consumption                | 196.7 VA  |
| Protective circuit                       | Transient surge protection; Varistor            |
| Power factor (cos phi)                   | 0.58  |
| Typical response time                    | < 0.5 s   |
| Input fuse                               | 4 A (slow-blow, internal)                       |
| Recommended breaker for input protection | 6 A ... 16 A (Characteristics B, C, D, K)       |

### Output data

|  |  |
|--|--|
| Efficiency   | > 88 % (for 230 V AC and nominal values)   |
| Output characteristic                              | U/I  |
| Nominal output voltage                             | 24 V DC  |
| Setting range of the output voltage ( $U_{Set}$ )  | 22.5 V DC ... 29.5 V DC (> 24 V DC, constant capacity restricted)  |
| Output current $I_{max}$                           | 6.5 A  |
| Nominal output current ( $I_N$ )                   | 4.2 A (-25 °C ... 55 °C)<br>4.4 A (-25 °C ... 40 °C permanent)   |
| Derating   | 55 °C ... 70 °C (2.5 %/K)  |
| Feedback voltage resistance                        | ≤ 35 V DC  |
| Protection against overvoltage at the output (OVP) | < 35 V DC  |
| Control deviation                                  | < 1 % (change in load, static 10 % ... 90 %)<br>< 2 % (change in load, dynamic 10 % ... 90 %)<br>< 0.1 % (change in input voltage ±10 %) |
| Residual ripple                                    | < 40 mV <sub>PP</sub> (20 MHz)   |
| Output power                                       | 100.8 W  |
| Peak switching voltages nominal load               | < 30 mV <sub>PP</sub> (20 MHz)   |
| Maximum no-load power dissipation                  | < 0.7 W  |

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

|                              |  |
|------------------------------|--|
| Power loss nominal load max. | 13.2 W                                     |
| Rise time                    | < 0.5 s ( $U_{OUT}$ (10 % ... 90 %))       |
| Connection in parallel       | yes, for redundancy and increased capacity |
| Connection in series         | yes  |

## Connection data

### Input

|                                       |                     |
|---------------------------------------|---------------------|
| Connection method                     | Screw connection    |
| Conductor cross section, rigid min.   | 0.2 mm <sup>2</sup> |
| Conductor cross section, rigid max.   | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible min. | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max. | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 12                  |
| Stripping length                      | 6.5 mm              |
| Screw thread                          | M3                  |
| Tightening torque, min                | 0.5 Nm              |
| Tightening torque max                 | 0.6 Nm              |

### Output

|                                       |                     |
|---------------------------------------|---------------------|
| Connection method                     | Screw connection    |
| Conductor cross section, rigid min.   | 0.2 mm <sup>2</sup> |
| Conductor cross section, rigid max.   | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible min. | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max. | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 12                  |
| Stripping length                      | 6.5 mm              |
| Screw thread                          | M3                  |
| Tightening torque, min                | 0.5 Nm              |
| Tightening torque max                 | 0.6 Nm              |

## Signaling

|                           |           |
|---------------------------|-----------|
| Types of signaling        | LED       |
| Operating voltage display | Green LED |

### Signal output: LED status indicator

|                        |                                   |
|------------------------|-----------------------------------|
| Status display         | "DC OK" LED green                 |
| Note on status display | $U_{OUT} > 21.5$ V: LED lights up |

## Electrical properties

|                                 |   |
|---------------------------------|---|
| Number of phases                | 1.00  |
| Insulation voltage input/output | 4 kV AC (type test)<br>3.75 kV AC (routine test)<br>3.75 kV AC (routine test) |

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit

2868664

<https://www.phoenixcontact.com/us/products/2868664>

|  |                     |
|--|---------------------|
|  | 4 kV AC (type test) |
|--|---------------------|


## Product properties

|                            |                    |
|----------------------------|--------------------|
| Product type               | Power supply       |
| Product family             | STEP POWER         |
| MTBF (IEC 61709, SN 29500) | > 897000 h (40 °C) |

## Insulation characteristics

|                      |                                |
|----------------------|--------------------------------|
| Protection class     | II (in closed control cabinet) |
| Overvoltage category | III                            |
| Degree of pollution  | 2                              |

## Dimensions

|  |   |
|--|---|
| Dimensional drawing                    |  |
| Width                                  | 90 mm   |
| Height                                 | 90 mm   |
| Depth Device depth (DIN rail mounting) | 55 mm (Device depth (DIN rail mounting))  |
| Horizontal pitch                       | 5 Div.  |

## Installation dimensions

|                                  |               |
|----------------------------------|---------------|
| Installation distance right/left | 0 mm / 0 mm   |
| Installation distance top/bottom | 30 mm / 30 mm |

## Mounting

|                         |  |
|-------------------------|--|
| Mounting type           | DIN rail mounting                              |
| Assembly instructions   | alignable: 0 mm horizontally, 30 mm vertically |
| Mounting position       | horizontal DIN rail NS 35, EN 60715            |
| With protective coating | No   |

## Material specifications

|                     |                        |
|---------------------|------------------------|
| Housing material    | Plastic                |
| Type of housing     | Polycarbonate          |
| Foot latch material | POM (Polyoxymethylene) |
| Housing material    | Polycarbonate          |

## Environmental and real-life conditions

### Ambient conditions

|                                 |  |
|---------------------------------|--|
| Degree of protection            | IP20   |
| Ambient temperature (operation) | -25 °C ... 70 °C (> 55° C derating : 2.5%/K) |

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

|  |  |
|--|--|
| Ambient temperature (storage/transport)        | -40 °C ... 85 °C   |
| Climatic class                                 | 3K3 (in acc. with EN 60721)  |
| Max. permissible relative humidity (operation) | ≤ 95 % (at 25 °C, non-condensing)  |
| Shock  | 18 ms, 30g, in each space direction (according to IEC 60068-2-27)                          |
| Vibration (operation)                          | < 15 Hz, amplitude ±2.5 mm (according to IEC 60068-2-6)<br>15 Hz ... 150 Hz, 2.3g, 90 min. |

## Standards and regulations

|  |  |
|--|--|
| Rail applications  | EN 50121-4                               |
| Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations | EN 50178/VDE 0160 (PELV)                 |
| Standard – Limitation of mains harmonic currents   | EN 61000-3-2                             |
| Standard - Electrical safety   | IEC 62368-1 (SELV)                       |
| Standard – Protection against shock currents, basic requirements for protective separation in electrical equipment               | EN 50178                                 |
| Standard – Safety extra-low voltage  | IEC 62368-1 (SELV) und EN 60204-1 (PELV) |
| Standard - Safe isolation  | DIN VDE 0100-410                         |
| Standard - Safety of transformers  | EN 61558-2-16                            |

## Approvals

|                       |  |
|-----------------------|--|
| CSA                   | CSA-C22.2 No. 107.1-01   |
| Shipbuilding approval | DNV GL (EMC B) ABS, NK   |
| UL approvals          | UL/C-UL listed UL 508<br>UL/C-UL Recognized UL 60950-1<br>UL ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D T4A (Hazardous Location) |

## Conformity/Approvals

|                                  |   |
|----------------------------------|---|
| SIL in accordance with IEC 61508 | 0 |
|----------------------------------|---|

## EMC data

|                                     |   |
|-------------------------------------|---|
| Low Voltage Directive               | Conformance with Low Voltage Directive 2014/35/EC |
| EMC requirements for noise emission | EN 61000-6-3<br>EN 61000-6-4                      |
| EMC requirements for noise immunity | EN 61000-6-1<br>EN 61000-6-2                      |
| Electromagnetic compatibility       | Conformance with EMC Directive 2014/30/EU         |

## Electrostatic discharge

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-2 |
|-----------------------|--------------|

## Electrostatic discharge

|                   |                            |
|-------------------|----------------------------|
| Contact discharge | ± 6 kV (Contact discharge) |
| Discharge in air  | ± 8 kV (Air discharge)     |
| Comments          | Criterion B                |

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

## Electromagnetic HF field

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-3 |
|-----------------------|--------------|

## Electromagnetic HF field

|                     |                   |
|---------------------|-------------------|
| Frequency range     | 80 MHz ... 1 GHz  |
| Test field strength | 10 V/m            |
| Frequency range     | 1.4 GHz ... 2 GHz |
| Test field strength | 3 V/m             |
| Frequency range     | 2 GHz ... 2.7 GHz |
| Test field strength | 1 V/m             |
| Comments            | Criterion A       |

## Fast transients (burst)

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-4 |
|-----------------------|--------------|

## Fast transients (burst)

|          |                                    |
|----------|------------------------------------|
| Input    | 2 kV (Test Level 3 - asymmetrical) |
| Output   | 2 kV (Test Level 3 - asymmetrical) |
| Comments | Criterion B                        |

## Surge voltage load (surge)

|                       |   |
|-----------------------|---|
| Standards/regulations | EN 61000-4-5  |
| Input                 | 2 kV (Test Level 3 - symmetrical)<br>4 kV (Test Level 4 - asymmetrical) |
| Output                | 1 kV (Test Level 2 - symmetrical)<br>1 kV (Test Level 2 - asymmetrical) |
| Comments              | Criterion A   |

## Conducted interference

|                       |              |
|-----------------------|--------------|
| Standards/regulations | EN 61000-4-6 |
|-----------------------|--------------|

## Conducted interference

|                 |                     |
|-----------------|---------------------|
| Frequency range | 10 kHz ... 80 MHz   |
| Comments        | Criterion A         |
| Voltage         | 10 V (Test Level 3) |

## Voltage dips

|                       |               |
|-----------------------|---------------|
| Standards/regulations | EN 61000-4-11 |
|-----------------------|---------------|

## Emitted interference

|  |   |
|--|---|
| Standards/regulations                            | EN 61000-6-3  |
| Radio interference voltage in acc. with EN 55011 | EN 55011 (EN 55022) class B used in industry and residential area / EMC 1 |
| Emitted radio interference in acc. with EN 55011 | EN 55011 (EN 55022) class B used in industry and residential area / EMC 1 |

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27040701 |
| ECLASS-12.0 | 27040701 |
| ECLASS-13.0 | 27040701 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002540 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|

# STEP-PS/ 1AC/24DC/4.2 - Power supply unit



2868664

<https://www.phoenixcontact.com/us/products/2868664>

## Environmental product compliance

|            |  |
|------------|--|
| REACH SVHC | Lead 7439-92-1   |
| China RoHS | Environmentally Friendly Use Period = 25;  |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)