

Industrial Ethernet Switch - FL SWITCH SFNT 6TX/2FX ST - 2891026

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Wide-temperature Ethernet switch, 6 TP RJ45 ports, 2 FO ports, 100 Mbps full duplex in ST-D format, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function, autocrossing function, reads QoS priority messages, accepts security frames

Your advantages

- ✓ Auto negotiation and autocrossing detection simplifies installation and setup
- ✓ Local diagnostic indicators with LEDs
- ✓ The switch also offers cable locking and port blocking
- ✓ Alarm contact for power supply and link status diagnostics
- ✓ QoS-prioritized (Quality of Service) messages
- ✓ Wide operating temperature range (-40°C ... +75°C)
- ✓ RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 588072 |
| GTIN | 4046356588072 |
| Weight per Piece (excluding packing) | 650.000 g |
| Custom tariff number | 85176200 |
| Country of origin | Taiwan |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
| | Use in potentially explosive areas is not permitted in China. |

Industrial Ethernet Switch - FL SWITCH SFNT 6TX/2FX ST - 2891026

Technical data

Dimensions

| | |
|--------|--------|
| Width | 50 mm |
| Height | 130 mm |
| Depth | 100 mm |

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 75 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 62 kPa ... 108 kPa (up to 4160 m above mean sea level) |
| Air pressure (storage/transport) | 62 kPa ... 108 kPa (up to 4160 m above mean sea level) |

Interfaces

| | |
|-------------------------------|--|
| Interface | Ethernet (RJ45) |
| No. of ports | 6 (RJ45 ports) |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 Mbps |
| Transmission length | 100 m (per segment) |
| Signal LEDs | Data receive, link status |
| Interface | Fiber optic interface |
| No. of ports | 2 (ST multi-mode) |
| Transmission physics | multi-mode fiberglass |
| Transmission speed | 100 Mbps (full duplex) |
| Transmission length | 12.1 km (fiberglass with F-G 62.5/125 0.7 dB/km F1000) |
| | 3.3 km (fiberglass with F-G 62.5/125 2.6 dB/km F600) |
| | 7.1 km (fiberglass with F-G 50/125 0.7 dB/km F1200) |
| | 3.1 km (fiberglass with F-G 50/125 1.6 dB/km F800) |
| Wavelength | 1300 nm |

Function

| | |
|----------------------------------|--|
| Basic functions | Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode, includes QoS and alarm contact |
| Additional functions | Autonegotiation |
| Status and diagnostic indicators | LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port |

Network expansion parameters

| | |
|---|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m |

Industrial Ethernet Switch - FL SWITCH SFNT 6TX/2FX ST - 2891026

Technical data

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC (redundant) |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 9 V DC ... 32 V DC |
| Typical current consumption | 250 mA (at U _S = 24 V DC) |

General

| | |
|------------------|---|
| Mounting type | DIN rail |
| Type AX | Block design |
| Net weight | 484 g |
| Housing material | Aluminum |
| MTTF | 43.9 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%) |

Standards and Regulations

| | |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2 |
| Conformance | CE-compliant |
| ATEX | # II 3 G Ex nA nC IIC T4 Gc |
| IECEX | Ex nA nC IIC T4 Gc |
| UL, USA/Canada | Class I, Div. 2, Groups A, B, C, D |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 10; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 19170402 |
| eCl@ss 11.0 | 19170402 |
| eCl@ss 4.0 | 27250500 |
| eCl@ss 4.1 | 27250500 |
| eCl@ss 5.0 | 19030100 |
| eCl@ss 5.1 | 19030100 |
| eCl@ss 6.0 | 19170100 |
| eCl@ss 7.0 | 19170106 |

Industrial Ethernet Switch - FL SWITCH SFNT 6TX/2FX ST - 2891026

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 9.0 | 19170106 |
|------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 6.0 | EC000734 |
| ETIM 7.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172901 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43222612 |
| UNSPSC 18.0 | 43222612 |
| UNSPSC 19.0 | 43222612 |
| UNSPSC 20.0 | 43222612 |
| UNSPSC 21.0 | 43222612 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / EAC / EAC / cULus Listed

Ex Approvals

IECEX / UL Listed / cUL Listed / ATEX / cULus Listed

Approval details


| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|-----------|--|---|---------------|

Industrial Ethernet Switch - FL SWITCH SFNT 6TX/2FX ST - 2891026


Approvals

| | | | |
|------------|---|---|---------------|
| cUL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
|------------|---|---|---------------|

| | | | |
|-----|---|--|---------------|
| EAC |  | | EAC-Zulassung |
|-----|---|--|---------------|

| | | | |
|-----|---|--|--------------------------|
| EAC |  | | RU *- DE.A*08.B.00739 |
|-----|---|--|--------------------------|

| | | | |
|-----|---|--|---------------------|
| EAC |  | | RU*-DE.*.B.00741/19 |
|-----|---|--|---------------------|

| | | | |
|--------------|---|--|--|
| cULus Listed |  | | |
|--------------|---|--|--|