

2891079

https://www.phoenixcontact.com/us/products/2891079

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Rack-mount managed Ethernet switch meets IEC 61850-3 and IEEE 1613. Provides eight RJ45 ports at 10/100 Mbps, 16 SC-D MM fiber ports at 100 Mbps and four gigabit combo ports (10/100/1000 Mbps RJ45 connection; 1000 Mbps fiber optic connection requires 1000 Mbps SFP module).



### Your advantages

- Network structure according to IEC 61850
- IEEE 1613

#### Commercial data

Item number	2891079
Packing unit	1 pc
Sales key	DN17
Product key	DNN125
Catalog page	Page 321 (C-6-2019)
GTIN	4046356801690
Weight per piece (including packing)	4,480 g
Weight per piece (excluding packing)	4,470 g
Customs tariff number	85176200
Country of origin	TW



2891079

https://www.phoenixcontact.com/us/products/2891079

## Technical data

#### **Dimensions**

Width	442 mm
Height	44 mm
Depth	375 mm

### Notes

#### Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the
	download area

## Mounting

#### Interfaces

### Ethernet (RJ45)

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	100 m
No. of channels	8 (RJ45 ports)

#### Fiber optic interface

Connection method	SC
Transmission speed	100 Mbps (Full duplex)
Transmission physics	multi-mode fiberglass
Transmission length	8 km (fiberglass with F-G 62.5/125 0.7 dB/km F1000)
	3.3 km (fiberglass with F-G 62.5/125 2.6 dB/km F600)
	9.6 km (fiberglass with F-G 50/125 0.7 dB/km F1200)
	5.3 km (fiberglass with F-G 50/125 1.6 dB/km F800)
Wavelength	1300/1310 nm
No. of channels	16 (Multi mode)

### Ethernet (RJ45/FO combo)

Connection method	SFP/RJ45
Note on the connection method	Auto negotiation and autocrossing (RJ45 interface)
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet RJ45 (10/100/1000 Mbps) or SFP (1000 Mbps)
No. of channels	4 (Combo ports)

### Product properties



2891079

System properties

Basic functions

Functionality

https://www.phoenixcontact.com/us/products/2891079

Product type	Switch
Product family	Managed Switch 4000
MTTF	7.3 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
	41.2 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
	19.8 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
Switch functions	
Basic functions	Store and forward switch, Extended Ring and IEEE redundancy Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
Redundancy	ERR (Extended ring redundancy)
Status and diagnostic indicators	LEDs: $\mathrm{U_{S1}}$ , $\mathrm{U_{S2}}$ (redundant voltage supply), link and activity per port
Security functions	
Basic functions	Store and forward switch, Extended Ring and IEEE redundancy Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
ectrical properties	
Transmission medium	Copper
	FO
Supply	
Power supply connection	From FL SWITCH 4800E-P
vironmental and real-life conditions  Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	-40 °C 70 °C
	-40 °C 70 °C -40 °C 85 °C
Ambient temperature (operation)	
Ambient temperature (operation)  Ambient temperature (storage/transport)	-40 °C 85 °C
Ambient temperature (operation)  Ambient temperature (storage/transport)  Permissible humidity (operation)	-40 °C 85 °C 5 % 95 % (non-condensing)
Ambient temperature (operation)  Ambient temperature (storage/transport)  Permissible humidity (operation)  Permissible humidity (storage/transport)	-40 °C 85 °C 5 % 95 % (non-condensing) 5 % 95 % (non-condensing)
Ambient temperature (operation)  Ambient temperature (storage/transport)  Permissible humidity (operation)  Permissible humidity (storage/transport)  Air pressure (operation)	-40 °C 85 °C 5 % 95 % (non-condensing) 5 % 95 % (non-condensing) 57 kPa 108 kPa (up to 4850 m above mean sea level)
Ambient temperature (operation)  Ambient temperature (storage/transport)  Permissible humidity (operation)  Permissible humidity (storage/transport)  Air pressure (operation)  Air pressure (storage/transport)	-40 °C 85 °C 5 % 95 % (non-condensing) 5 % 95 % (non-condensing) 57 kPa 108 kPa (up to 4850 m above mean sea level)

Store and forward switch, Extended Ring and IEEE redundancy,



2891079

https://www.phoenixcontact.com/us/products/2891079

		Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
Signaling		
	Status display	LEDs: $U_{S1}$ , $U_{S2}$ (redundant voltage supply), link and activity per port



2891079

https://www.phoenixcontact.com/us/products/2891079

## Classifications

UNSPSC 21.0

### **ECLASS**

	ECLASS-11.0	19170401
	ECLASS-12.0	19170401
	ECLASS-13.0	19170401
ETIM		
	ETIM 9.0	EC000734
UNSPSC		

43222600



2891079

https://www.phoenixcontact.com/us/products/2891079

## Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com