2900753

https://www.phoenixcontact.com/us/products/2900753



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 9 CONTACTRON modules, with screw connection and 22.5 mm housing width, connecting cable: 0.3 m, with ferrules.



### Your advantages

- Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

### Commercial data

Item number	2900753
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
Catalog page	Page 38 (C-5-2019)
GTIN	4046356528511
Weight per piece (including packing)	195.2 g
Weight per piece (excluding packing)	160.5 g
Customs tariff number	85444290
Country of origin	DE

#### 2900753

https://www.phoenixcontact.com/us/products/2900753



### Technical data

#### Product properties

Product type	Loop bridge			
Product family	CONTACTRON			
Number of bridgeable modules	9			
Electrical properties				
Operating voltage range	42 V AC 575 V AC			
Operating current	≤ 25 A			
Cable/line				
Connecting cable length	0.3 m			
Cable cross section	2.5 mm <sup>2</sup>			

2900753 https://www.phoenixcontact.com/us/products/2900753 **PHŒNIX** CONTACT

## Classifications

### ECLASS

ECLASS-11.0	27371392
ECLASS-12.0	27371392
ECLASS-13.0	27371392

### ETIM

	ETIM 9.0	EC002498	
UNSPSC			
	UNSPSC 21.0	39121100	

2900753 https://www.phoenixcontact.com/us/products/2900753



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com