

https://www.phoenixcontact.com/us/products/2901544



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 5 CONTACTRON modules, with screw connection and 22.5 mm housing width, connecting cable: 1 m $\,$



Your advantages

- Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- · Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

Commercial data

Item number	2901544
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
GTIN	4046356610292
Weight per piece (including packing)	178.1 g
Weight per piece (excluding packing)	159.1 g
Customs tariff number	85444290
Country of origin	DE



https://www.phoenixcontact.com/us/products/2901544



Technical data

Product properties

Loop bridge
CONTACTRON
5
42 V AC 575 V AC

Color

Color	gray (RAL 7042)
Cable/line	

Cable/line



https://www.phoenixcontact.com/us/products/2901544



Classifications

ECLASS

	ECLASS-11.0	27371392	
	ECLASS-12.0	27371392	
	ECLASS-13.0	27371392	
ETIM			
	ETIM 9.0	EC002498	

UNSPSC



https://www.phoenixcontact.com/us/products/2901544



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com