2901545

https://www.phoenixcontact.com/us/products/2901545



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 5 CONTACTRON modules, with screw connection and 22.5 mm housing width, connecting cable: 3 m $\,$



Your advantages

- Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

Commercial data

Item number	2901545
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
Catalog page	Page 39 (C-5-2019)
GTIN	4046356610285
Weight per piece (including packing)	362.9 g
Weight per piece (excluding packing)	330.7 g
Customs tariff number	85444290
Country of origin	DE

2901545

https://www.phoenixcontact.com/us/products/2901545



Technical data

Product properties

Product type	Loop bridge	
Product family	CONTACTRON	
Number of bridgeable modules	5	
Electrical properties		
Operating voltage range	42 V AC 575 V AC	
Operating current	≤ 25 A	
Connection data		
Connection method	Screw connection	
Dimensions		
Width	22.5 mm	
Material specifications		
Color	gray (RAL 7042)	
Cable/line		
Connecting cable length	3 m	
Cable cross section	2.5 mm ²	

2901545

https://www.phoenixcontact.com/us/products/2901545



Classifications

ECLASS

ECLASS-11.0	27371392
ECLASS-12.0	27371392
ECLASS-13.0	27371392

ETIM

	ETIM 9.0	EC002498	
UNSPSC			
	UNSPSC 21.0	39121100	

2901545 https://www.phoenixcontact.com/us/products/2901545



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com