

https://www.phoenixcontact.com/us/products/2901698



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 7 CONTACTRON modules, with screw connection and 22.5 mm housing width, connecting cable: $3\ m$



Your advantages

- Only suitable for CONTACTRON series with screw connection ELR H3...-SC-..., ELR H5...-SC-..., EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- · Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

Commercial data

Item number	2901698
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
Catalog page	Page 39 (C-5-2019)
GTIN	4046356624633
Weight per piece (including packing)	398.5 g
Weight per piece (excluding packing)	361.4 g
Customs tariff number	85444290
Country of origin	DE



https://www.phoenixcontact.com/us/products/2901698



Technical data

Product properties

Product type	Loop bridge
Product family	CONTACTRON
Number of bridgeable modules	7
ectrical properties	

Ele

Operating voltage range	42 V AC 575 V AC
Operating current	≤ 25 A

Connection data

Dimensions

Material specifications

Color	gray (RAL 7042)
-------	-----------------

Cable/line

Connecting cable length	3 m
Cable cross section	2.5 mm²



https://www.phoenixcontact.com/us/products/2901698



Classifications

ECLASS

ECLASS-11.0	27371392	
ECLASS-12.0	27371392	
ECLASS-13.0	27371392	
ETIM		
ETIM 9.0	EC002498	

UNSPSC

UNSPSC 21.0 3912	21100
------------------	-------



https://www.phoenixcontact.com/us/products/2901698



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com