


FLK 20/2FLK14/EZ-DR/500/KONFEK - Cable



2902707

<https://www.phoenixcontact.com/us/products/2902707>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; connection 1: IDC/FLK socket strip (1x 20-position); connection 2: IDC/FLK socket strip (2x 14-position); cable length: 5 m

Your advantages

- Suitable for connecting 16-channel digital cards, e.g., SIMATIC[®] ET 200SP
- The 16 digital signals are split into 2x 8 signals on the field side
- IDC/FLK connector: 20-pos. to two 14-pos. (in accordance with IEC 60603-13)

Commercial data

Item number	2902707
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK2152
GTIN	4046356671538
Weight per piece (including packing)	418.8 g
Weight per piece (excluding packing)	418.8 g
Customs tariff number	85444290
Country of origin	DE

Technical data

Product properties

Product type	System cable
--------------	--------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation)
	-10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A (Uncoiled, see derating)
Current (Per path, 70°C)	≤ 0.6 A (Uncoiled, see derating)

Supported controller EMERSON DeltaV

Suitable I/O card	VE4001S2T2B5
	VE4002S1T2B6

Supported controller SIEMENS ET 200SP

Suitable base unit	6ES7193-6BP00-0BA0
	6ES7193-6BP00-2BA0
	6ES7193-6BP00-0BA1
	6ES7193-6BP00-0DA0
	6ES7193-6BP00-2DA0
	6ES7193-6BP00-0DA1
Suitable I/O module	6ES7131-6BH01-0BA0 (Base Units A0/A1)
	6ES7131-6BH01-2BA0 (Base Units A0/A1)
	6ES7132-6BH01-0BA0 (Base Units A0/A1)
	6ES7132-6BH01-2BA0 (Base Units A0/A1)

Cable/line

Cable length	5 m
--------------	-----

20X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	20
Shielded	no

FLK 20/2FLK14/EZ-DR/500/KONFEK - Cable



2902707

<https://www.phoenixcontact.com/us/products/2902707>

Cable type	20X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	20x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	7.60 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	64 mm
Smallest bending radius, movable installation	120 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
IDC/FLK20 (1)	IDC/FLK14-1 (1) = black
IDC/FLK20 (2)	IDC/FLK14-1 (2) = brown
IDC/FLK20 (3)	IDC/FLK14-1 (3) = red
IDC/FLK20 (4)	IDC/FLK14-1 (4) = orange
IDC/FLK20 (5)	IDC/FLK14-1 (5) = yellow
IDC/FLK20 (6)	IDC/FLK14-1 (6) = green
IDC/FLK20 (7)	IDC/FLK14-1 (7) = blue
IDC/FLK20 (8)	IDC/FLK14-1 (8) = violet
IDC/FLK20 (9)	IDC/FLK14-2 (1) = gray
IDC/FLK20 (10)	IDC/FLK14-2 (2) = white
IDC/FLK20 (11)	IDC/FLK14-2 (3) = white-black
IDC/FLK20 (12)	IDC/FLK14-2 (4) = white-brown
IDC/FLK20 (13)	IDC/FLK14-2 (5) = white-red
IDC/FLK20 (14)	IDC/FLK14-2 (6) = white-orange
IDC/FLK20 (15)	IDC/FLK14-2 (7) = white-yellow
IDC/FLK20 (16)	IDC/FLK14-2 (8) = white-green
IDC/FLK20 (17)	IDC/FLK14-2 (9) = white-blue
IDC/FLK20 (18)	IDC/FLK14-2 (10) = white-violet
IDC/FLK20 (19)	IDC/FLK14-1 (9) = white-gray
IDC/FLK20 (20)	IDC/FLK14-1 (10) = brown-black

Connection data

FLK 20/2FLK14/EZ-DR/500/KONFEK - Cable



2902707

<https://www.phoenixcontact.com/us/products/2902707>

Connection 1

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	20
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Connection 2

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	2
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

2902707

<https://www.phoenixcontact.com/us/products/2902707>

Classifications

ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

ETIM

ETIM 9.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

FLK 20/2FLK14/EZ-DR/500/KONFEK - Cable



2902707

<https://www.phoenixcontact.com/us/products/2902707>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com