

FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Passive network isolator for electrical isolation in Ethernet networks. For the protection of Ethernet devices against potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Ethernet connection via two M12 sockets (D-coded).

Product description

The FL ISOLATOR 100-M12 has been specifically developed for use in the railway industry. Featuring M12 connection technology and optional wall mounting, this network isolator can be used flexibly.

Your advantages

- No power supply required
- Dielectric strength of up to 4 kV
- Continuous insulation voltage of 250 VRMS
- Protection against aggressive environmental influences, particularly harsh industrial environments, thanks to coated PCB
- Approval for railway applications (rolling stock) in accordance with EN 50155 and EN 50121
- Wall mounting
- Extended temperature range of -40 °C ... +75 °C

Commercial data

Item number	2902985
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	DNC332
Catalog page	Page 365 (C-6-2019)
GTIN	4046356727815
Weight per piece (including packing)	145.7 g
Weight per piece (excluding packing)	149.6 g
Customs tariff number	85176990
Country of origin	DE

FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Technical data

Product properties

Product type	Network isolator
MTTF	18372 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
	13381 Years (SN 29500 standard, temperature 40°C, operating cycle 34.25%)
	3348 Years (SN 29500 standard, temperature 40°C, operating cycle 100%)
MTBF	38062 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
	12264 Years (Telcordia standard, 40°C temperature, 34.25% operating cycle (5 days a week, 12 hours a day))

Electrical properties

Electrical isolation	Port X1//port X2
Insulation voltage input/output	250 V _{rms}
Test voltage data interface/data interface	4 kV AC (50 Hz, 1 min.)

Supply

Supply voltage range	passive module, no supply voltage required
----------------------	--

Interfaces

Signal	Ethernet
	PROFINET

Data: Ethernet interface, 10/100Base-T(X) in accordance with IEEE 802.3

Serial transmission speed	10/100 Mbps
Connection method	M12 connectors (D-coded, female)
No. of channels	1
Tightening torque	≤ 2 Nm
Transmission length	≤ 100 m (Total length across both ports (dependent on data rate and cable used))
Protocols supported	Transparent protocol for IPv4 and IPv6

Data: Ethernet interface, 10/100Base-T(X) in accordance with IEEE 802.3

Connection method	M12 connectors (D-coded, female)
No. of channels	1

Dimensions


FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Dimensional drawing



Width	66 mm
Height	91 mm
Depth	34 mm

Material specifications

Color (Housing)	black (RAL 9005)
Material Upper part	Polycarbonate PC
Material Lower part	PC/ABS

Cable/line

Shielding	no connection to protective earth ground (PE)
	capacitive isolation between both shield connections

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C ... 75 °C (85°C for 10 min.; thereafter function can no longer be guaranteed - check device)
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Altitude	≤ 5000 m (For restrictions, see the manufacturer's declaration for altitude operation)
Permissible humidity (operation)	10 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %

Approvals

CE

Certificate	CE-compliant
-------------	--------------

Corrosive gas test

Identification	ISA-S71.04-1985 G3 Harsh Group A
----------------	----------------------------------

EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

Fast transients (burst)

Standards/regulations	EN 61000-4-4
-----------------------	--------------

FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Emitted interference	
Standards/regulations	EN 61000-6-4
Radio interference voltage in acc. with EN 55011	Class B, area of application: Industry and residential
Emitted radio interference in acc. with EN 55011	Class B, area of application: Industry and residential

Standards and regulations

Standards/regulations	EN 50121 and EN 50155 (for railway applications)
	IEC 60571
	IEC 62368
	Suitable in accordance with SELV EN 50153

Mounting

Mounting type	Wall mounting
Mounting position	Wall mounting

FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Classifications

ECLASS

ECLASS-11.0	27240692
ECLASS-13.0	27240692
ECLASS-12.0	27240692

ETIM

ETIM 9.0	EC002584
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

FL ISOLATOR 100-M12 - Network isolator



2902985

<https://www.phoenixcontact.com/us/products/2902985>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com