

# EMD-BL-C-10 - Monitoring relay



2903521

<https://www.phoenixcontact.com/us/products/2903521>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Monitoring relay for monitoring single-phase currents of 0 ... 5 A AC or 0 ... 10 A AC, overcurrent/undercurrent or window, 1 changeover contact, with screw connection

## Product description

Safety and system availability requirements are constantly on the increase – across all industries. Processes are becoming more and more complex, not only in machine building and the chemical industry but also in building technology. The demands placed on energy technology are also constantly on the rise.

It is only by continuously monitoring key network and system parameters that error-free and therefore cost-effective operation can be achieved. Electronic monitoring relays from the EMD series are available for a wide range of monitoring tasks so that the consequences of errors can be avoided or kept within limits.

The operating states are signaled via color LEDs and any errors that occur can be sent to a controller via a floating contact or can shut down a section of the system. All device versions are equipped with response delays so that measured values outside the set monitoring range can be briefly tolerated.

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2903521             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | C440                |
| Product key                          | CK4221              |
| Catalog page                         | Page 246 (C-5-2019) |
| GTIN                                 | 4046356747257       |
| Weight per piece (including packing) | 79.1 g              |
| Weight per piece (excluding packing) | 79.1 g              |
| Customs tariff number                | 85364900            |
| Country of origin                    | AT                  |

# EMD-BL-C-10 - Monitoring relay

2903521

<https://www.phoenixcontact.com/us/products/2903521>



## Technical data

### Product properties

|                         |                            |
|-------------------------|----------------------------|
| Product type            | Current monitoring relay   |
| Operating mode          | 100% operating factor      |
| Mechanical service life | 15x 10 <sup>6</sup> cycles |

### Insulation characteristics

|            |                  |
|------------|------------------|
| Insulation | Basic insulation |
|------------|------------------|

### Insulation characteristics

|                      |                  |
|----------------------|------------------|
| Insulation           | Basic insulation |
| Overvoltage category | III              |
| Pollution degree     | 2                |

### Electrical properties

|                          |                           |
|--------------------------|---------------------------|
| Service life electrical  | 1x 10 <sup>5</sup> cycles |
| Mains type               | 1-phase                   |
| Rated insulation voltage | 300 V (Supply circuit)    |
|                          | 250 V (Output circuit)    |
|                          | 300 V (Measuring circuit) |
| Rated surge voltage      | 4 kV                      |

### Supply

|                           |                           |
|---------------------------|---------------------------|
| Supply voltage            | 230 V AC ±15 %            |
| Supply voltage range      | 195.5 V AC ... 264.5 V AC |
| Nominal power consumption | 5 VA (0.8 W)              |

### Input data

|                                  |                                       |
|----------------------------------|---------------------------------------|
| Input name                       | Measuring input                       |
| Measured value                   | AC sine (48 Hz ... 63 Hz)             |
| Input current range              | 0 A ... 5 A                           |
|                                  | 0 A ... 10 A                          |
|                                  | Configurable via rotary switches      |
| Overload capacity                | 13 A AC                               |
| Input resistance current input   | 3 mΩ                                  |
| Frequency range                  | 48 Hz ... 63 Hz                       |
| Maximum temperature coefficient  | ≤ 0.05 %                              |
| Setting range for response delay | 0.1 s ... 10 s                        |
| Min. setting range               | 5 % ... 95 % (from I <sub>N</sub> )   |
| Max. setting range               | 10 % ... 100 % (from I <sub>N</sub> ) |
| Function                         | Overcurrent                           |
|                                  | Undercurrent                          |
|                                  | Window                                |
| Basic accuracy                   | ≤ 5 % (of the nominal value)          |

# EMD-BL-C-10 - Monitoring relay



2903521

<https://www.phoenixcontact.com/us/products/2903521>

|                  |                              |
|------------------|------------------------------|
| Setting accuracy | ± 5 % (of the nominal value) |
| Repeat accuracy  | ≤ 2 %                        |
| Recovery time    | > 500 ms                     |

## Output data

### Switching

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Contact switching type                | 1 floating changeover contact       |
| Maximum switching voltage             | 250 V AC (in acc. with IEC 60664-1) |
| Interrupting rating (ohmic load) max. | 1250 VA (5 A / 250 V AC)            |
| Output fuse                           | 5 A (fast-blow)                     |

## Connection data

|                                  |                     |
|----------------------------------|---------------------|
| Connection method                | Screw connection    |
| Stripping length                 | 8 mm                |
| Conductor cross section rigid    | 0.5 mm² ... 2.5 mm² |
| Conductor cross section flexible | 0.5 mm² ... 2.5 mm² |
| Conductor cross section AWG      | 20 ... 14           |
| Tightening torque                | 1 Nm ... 1 Nm       |

## Signaling

|                           |            |
|---------------------------|------------|
| Status display            | Yellow LED |
| Operating voltage display | Green LED  |
| Error indication          | Red LED    |

## Dimensions

|        |         |
|--------|---------|
| Width  | 17.5 mm |
| Height | 89.5 mm |
| Depth  | 65.5 mm |

## Material specifications

|                             |                                      |
|-----------------------------|--------------------------------------|
| Color                       | gray (RAL 7042)                      |
| Housing insulation material | Polyamide PA 6.6, self-extinguishing |

## Environmental and real-life conditions

### Ambient conditions

|   |                                   |
|---|-----------------------------------|
| Degree of protection (Housing)                    | IP40 (Housing)                    |
| Degree of protection (Connection terminal blocks) | IP20 (Connection terminal blocks) |
| Ambient temperature (operation)                   | -25 °C ... 55 °C                  |
| Ambient temperature (storage/transport)           | -25 °C ... 70 °C                  |
| Climatic class                                    | 3K3 (in acc. with EN 60721)       |
| Permissible humidity (operation)                  | 15 % ... 85 %                     |

## Approvals

# EMD-BL-C-10 - Monitoring relay



2903521

<https://www.phoenixcontact.com/us/products/2903521>

## CE

|             |              |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

## UL, USA/Canada

|                |                       |
|----------------|-----------------------|
| Identification | UL/C-UL Listed UL 508 |
|----------------|-----------------------|

## EMC data

|                               |  |
|-------------------------------|--|
| Low Voltage Directive         | Conformance with Low Voltage Directive |
| Noise immunity                | EN 61000-6-2                           |
| Electromagnetic compatibility | Conformance with EMC directive         |
| Noise emission                | EN 61000-6-3                           |

## Standards and regulations

|                       |                  |
|-----------------------|------------------|
| Standards/regulations | DIN EN 60947-5-1 |
|-----------------------|------------------|

## Mounting

|                       |  |
|-----------------------|--|
| Mounting type         | DIN rail mounting                                      |
| Assembly instructions | on standard DIN rail NS 35 in accordance with EN 60715 |
| Mounting position     | any  |

# EMD-BL-C-10 - Monitoring relay



2903521

<https://www.phoenixcontact.com/us/products/2903521>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27371802 |
| ECLASS-12.0 | 27371802 |
| ECLASS-13.0 | 27371802 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001440 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 41113600 |
|-------------|----------|

# EMD-BL-C-10 - Monitoring relay



2903521  
<https://www.phoenixcontact.com/us/products/2903521>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)