

# FLKM-M12/M/5P/SCO - Interface module




2903609

<https://www.phoenixcontact.com/us/products/2903609>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE module, with spring-cage terminal blocks and M12-SAC plug, 5-pos.



## Commercial data

Item number	2903609
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	NULL
Product key	CK225Y
GTIN	4046356753050
Weight per piece (including packing)	52.28 g
Weight per piece (excluding packing)	52.28 g
Customs tariff number	85369010
Country of origin	DE

# FLKM-M12/M/5P/SCO - Interface module



2903609

<https://www.phoenixcontact.com/us/products/2903609>

## Technical data

### Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	5

### Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

### Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

### Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 30 V DC
Current (per branch)	≤ 4 A

### Air clearances and creepage distances

Rated insulation voltage	50 V
Rated surge voltage	0.5 kV (1.2/50 μs)

### Connection data

#### Connection 1

Connection in acc. with standard	IEC 61076-2-101
Connection method	Pin
Type	M12
Number of connections	1
Number of positions	5

#### Connection 2

Connection method	Spring-cage connection
Stripping length	7 mm
Number of positions	6
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 14

### Signaling

Status display present	No
------------------------	----

### Dimensions

#### Item dimensions

# FLKM-M12/M/5P/SCO - Interface module



2903609

<https://www.phoenixcontact.com/us/products/2903609>

Width	27 mm
Height	90 mm
Depth	60 mm

## Material specifications

Color	green (RAL 6021)
Housing insulation material	Polyamide PA non-reinforced

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Module)	IP00
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-20 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Altitude	≤ 2000 m

## Approvals

### UKCA

Certificate	UKCA-compliant
-------------	----------------

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

# FLKM-M12/M/5P/SCO - Interface module



2903609

<https://www.phoenixcontact.com/us/products/2903609>

## Classifications

### ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

### ETIM

ETIM 9.0	EC002780
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# FLKM-M12/M/5P/SCO - Interface module



2903609

<https://www.phoenixcontact.com/us/products/2903609>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)