2904493

https://www.phoenixcontact.com/us/products/2904493



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

3-phase loop bridge for 5 CONTACTRON modules, with Push-in connection and 22.5 mm housing width, connecting cable: 3 m  $\,$ 



#### Your advantages

- · Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

#### Commercial data

Item number	2904493
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK74Z1
Catalog page	Page 39 (C-5-2019)
GTIN	4046356845281
Weight per piece (including packing)	369 g
Weight per piece (excluding packing)	333.1 g
Customs tariff number	85444290
Country of origin	DE

2904493

https://www.phoenixcontact.com/us/products/2904493



### Technical data

#### Product properties

Product type	Loop bridge	
Product family	CONTACTRON	
Number of bridgeable modules	5	
Electrical properties		

Operating voltage range	42 V AC 575 V AC
Operating current	≤ 25 A

#### Material specifications

Color	gray (RAL 7042)

#### Cable/line

Connecting cable length	3 m
Cable cross section	2.5 mm <sup>2</sup>

2904493

https://www.phoenixcontact.com/us/products/2904493



### Classifications

#### ECLASS

ECLASS-11.0	27371392
ECLASS-12.0	27371392
ECLASS-13.0	27371392

#### ETIM

	ETIM 9.0	EC002498
UNSPSC		
	UNSPSC 21.0	39121100

2904493 https://www.phoenixcontact.com/us/products/2904493



### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com