

EMG 45-DIO14M/LP - Diode block



2950132

<https://www.phoenixcontact.com/us/products/2950132>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Lamp test module, 2 diodes with common cathode: with 7 pairs, with common triggering



Commercial data

Item number	2950132
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	C440
Product key	CK4M11
Catalog page	Page 267 (C-5-2019)
GTIN	4017918083984
Weight per piece (including packing)	86.886 g
Weight per piece (excluding packing)	86 g
Customs tariff number	85411000
Country of origin	DE

EMG 45-DIO14M/LP - Diode block



2950132

<https://www.phoenixcontact.com/us/products/2950132>

Technical data

Product properties

Product type	Lamp testing module
--------------	---------------------

Insulation characteristics

Pollution degree	2
------------------	---

Input data

Diode

Description of the input	14 diodes, groups of 2 diodes with common cathode. Version: With 7 pairs, with common triggering
Diode type	1 N 4007
Max. operating voltage U_{max}	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	$\leq 5 \mu\text{A}$
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	0.7 A (with single load) 0.2 A (with simultaneous loads)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Width	45 mm
Height	75 mm
Depth	55 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Approvals

CE

EMG 45-DIO14M/LP - Diode block



2950132

<https://www.phoenixcontact.com/us/products/2950132>

Certificate	CE-compliant
Note	and EN 61326

Standards and regulations

Standards/regulations	DIN EN 50178
-----------------------	--------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

EMG 45-DIO14M/LP - Diode block



2950132

<https://www.phoenixcontact.com/us/products/2950132>

Classifications

ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

ETIM

ETIM 9.0	EC002278
----------	----------

UNSPSC

UNSPSC 21.0	32151500
-------------	----------

EMG 45-DIO14M/LP - Diode block



2950132

<https://www.phoenixcontact.com/us/products/2950132>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com