EMG 90-DIO 17E - Diode block

2954895

https://www.phoenixcontact.com/us/products/2954895

PHŒNIX

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Diode module, with 17 diodes, individually wired, diode type 1N 4007

Your advantages

- · Electrical decoupling of messages in fault reporting systems
- Spark-suppression diodes for limiting surge voltages of inductive loads

Commercial data

Item number	2954895
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	C440
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918085179
Weight per piece (including packing)	166.34 g
Weight per piece (excluding packing)	166.34 g
Customs tariff number	85411000
Country of origin	DE



2954895

https://www.phoenixcontact.com/us/products/2954895



Technical data

Product properties

Product type	Diode module	
Insulation characteristics		

Input data

Diode

Description of the input	17 diodes, individually connected
Diode type	1 N 4007
Max. operating voltage U _{max}	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	5 μΑ
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	0.7 A (with single load)
	0.5 A (with simultaneous loads)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² 4 mm ²
Conductor cross section flexible	0.2 mm ² 2.5 mm ²
Conductor cross section AWG	24 12

Dimensions

Width	90 mm
Height	75 mm
Depth	55 mm

Material specifications

Color green (RAL 6021)	
------------------------	--

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 70 °C

Approvals

~	-
- C.	⊢
-	_

Certificate CE-compliant

EMG 90-DIO 17E - Diode block

2954895

https://www.phoenixcontact.com/us/products/2954895



Note	and EN 61326	
Standards and regulations		
Standards/regulations	DIN EN 50178	
Mounting		
Mounting type	DIN rail mounting	
Assembly instructions	to an end of the second s	
Assembly instructions	in rows with zero spacing	



2954895

https://www.phoenixcontact.com/us/products/2954895



Classifications

ECLASS

ECLASS-11.0	27371010
ECLASS-12.0	27371010
ECLASS-13.0	27371010

ETIM

	ETIM 9.0	EC002278
UN	NSPSC	
	UNSPSC 21.0	32151500



2954895

https://www.phoenixcontact.com/us/products/2954895



Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com