

2954918

https://www.phoenixcontact.com/us/products/2954918

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Diode module, for extension with 32 1N 4007 diodes, common cathode

Your advantages

- Spark-suppression diodes for limiting surge voltages of inductive loads
- Electrical decoupling of messages in fault reporting systems

Commercial data

Item number	2954918
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	C440
Product key	CK4M11
Catalog page	Page 266 (C-5-2019)
GTIN	4017918085186
Weight per piece (including packing)	166.5 g
Weight per piece (excluding packing)	166.5 g
Customs tariff number	85411000
Country of origin	DE



https://www.phoenixcontact.com/us/products/2954918



Technical data

Product properties

Product type	Diode module
Insulation characteristics	
Pollution degree	2

Input data

Diode

Description of the input	32 diodes, common cathodes
Diode type	1 N 4007
Max. operating voltage U _{max}	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	5 μΑ
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	0.7 A (with single load)
	0.2 A (with simultaneous loads)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² 4 mm²
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 12

Dimensions

Width	90 mm
Height	75 mm
Depth	55 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 70 °C

Approvals

CE

Certificate	CE-compliant



2954918

https://www.phoenixcontact.com/us/products/2954918

Note	and EN 61326		
Standards and regulations			
Standards/regulations	DIN EN 50178		
Mounting			
Mounting type	DIN rail mounting		
Assembly instructions	in rows with zero spacing		
Mounting position	any		



2954918

https://www.phoenixcontact.com/us/products/2954918

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27371010
	ECLASS-12.0	27371010
	ECLASS-13.0	27371010
ETIM		
	ETIM 9.0	EC002278
UNSPSC		

32151500



https://www.phoenixcontact.com/us/products/2954918



Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com