

PSR-SCP- 24UC/ESM4/3X1/1X2/B - Safety relays



2963776

<https://www.phoenixcontact.com/us/products/2963776>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Safety relay for emergency stop and safety door monitoring up to SIL 3 or Cat. 4, PL e in accordance with EN ISO 13849, 2-channel operation, 3 enabling current paths, nominal input voltage: 24 V DC, plug-in screw terminal block

Your advantages

- Up to Cat. 4/PL e in accordance with EN ISO 13849-1, SIL 3 in accordance with EN IEC 62061, SIL 3 in accordance with IEC 61508
- 2 channel control
- 3 enabling current paths, 1 signaling current path
- Manual and monitored activation

Commercial data

| | |
|--------------------------------------|-------------------|
| Item number | 2963776 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DN01 |
| Product key | DNA112 |
| Catalog page | Page 21 (IF-2009) |
| GTIN | 4017918823627 |
| Weight per piece (including packing) | 192.3 g |
| Weight per piece (excluding packing) | 192.1 g |
| Customs tariff number | 85371098 |
| Country of origin | DE |

Technical data

Product properties

| | |
|-------------------------|--|
| Product type | Safety relays |
| Product family | PSRclassic |
| Application | Emergency stop |
| | Safety door |
| Mechanical service life | approx. 10^7 cycles |
| Relay type | Electromechanical relay with force-guided contacts in accordance with IEC/EN 61810-3 |

Electrical properties

| | |
|---|---|
| Maximum power dissipation for nominal condition | 16.44 W ($U_S = 26.4$ V, $I_L^2 = 72$ A ² , $P_{Total\ max} = 2.04$ W + 14.4 W) |
| Nominal operating mode | 100% operating factor |

Air clearances and creepage distances between the power circuits

| | |
|--------------------------------|---------------------------------------|
| Rated insulation voltage | 250 V |
| Rated surge voltage/insulation | See section "Insulation coordination" |

Input data

General

| | |
|---|--|
| Rated control circuit supply voltage U_S | 24 V DC -15 % / +10 % |
| Power consumption at U_S | typ. 1.68 W (DC) |
| Rated control supply current I_S | typ. 70 mA |
| Input voltage range in reference to U_N | 0.85 ... 1.1 |
| Typical input current at U_N | 70 mA DC |
| Inrush current | < 3.5 A ($\Delta t = 3$ ms at U_S) |
| | < 100 mA ($\Delta t = 500$ ms, with U_S/I_x at S12) |
| | > -100 mA ($\Delta t = 300$ ms, with U_S/I_x at S22) |
| | < 6 mA (with U_S/I_x to S34) |
| Current consumption | typ. 38 mA (S12) |
| | typ. -38 mA (S22) |
| | typ. 1 mA (with U_S/I_x to S34) |
| Voltage at input/start and feedback circuit | approx. 24 V DC |
| Filter time | 5 ms (at A1 in the event of voltage dips at U_S) |
| | No test pulses permitted |
| Typical response time | 100 ms (Monitored/manual start) |
| Typical release time | 20 ms (on demand via the sensor circuit) |
| | 45 ms (on demand via A1) |
| Concurrence | ∞ |
| Recovery time | 1 s (following demand of the safety function) |
| | < 1 s (Boot time) |
| Protective circuit | Surge protection; Suppressor diode |
| Max. permissible overall conductor resistance | approx. 50 Ω (Input and start circuits at U_S) |

PSR-SCP- 24UC/ESM4/3X1/1X2/B - Safety relays



2963776

<https://www.phoenixcontact.com/us/products/2963776>

| | |
|---------------------------|-----------|
| Operating voltage display | Green LED |
| Status display | Green LED |

Output data

| | |
|---|--|
| Contact switching type | 3 enabling current paths |
| | 1 signaling current path |
| Contact material | AgSnO ₂ , + 0.2 µm Au |
| Maximum switching voltage | 250 V AC |
| Minimum switching voltage | 10 V AC/DC |
| Limiting continuous current | 6 A (N/O contact) |
| Maximum inrush current | 6 A |
| Inrush current, minimum | 10 mA |
| Sq. Total current | 72 A ² (Enabling current paths) |
| | 36 A ² (Signaling current path 41/42) |
| Interrupting rating (ohmic load) max. | see load limit curve |
| Switching capacity min. | 100 mW |
| Switching capacity in accordance with IEC 60947-5-1 | 6 A (DC13, enabling current paths) |
| | 5 A (AC15, enabling current paths) |
| | 2 A (DC13, signaling current paths) |
| | 1.5 A (AC15, signaling current paths) |
| Output fuse | 10 A gL/gG (Enabling current paths) |
| | 4 A gL/gG (Low-demand enabling current paths) |
| | 6 A gL/gG (Signaling current path) |

Connection data

Connection technology

| | |
|-----------|-----|
| pluggable | yes |
|-----------|-----|

Conductor connection

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Conductor cross section rigid | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross-section AWG | 24 ... 12 |
| Stripping length | 7 mm |
| Screw thread | M3 |

Dimensions

| | |
|--------|----------|
| Width | 22.5 mm |
| Height | 99 mm |
| Depth | 114.5 mm |

Material specifications

| | |
|------------------|-------------------|
| Color (Housing) | yellow (RAL 1018) |
| Housing material | Polyamide |

Characteristics

Safety data

| | |
|---------------|---|
| Stop category | 0 |
|---------------|---|

Safety data: EN ISO 13849

| | |
|------------------------|--|
| Category | 4 |
| Performance level (PL) | e (5 A DC13; 5 A AC15; 8760 switching cycles/year) |

Safety data: IEC 61508 - High demand

| | |
|------------------------------|---|
| Safety Integrity Level (SIL) | 3 |
|------------------------------|---|

Safety data: IEC 61508 - Low demand

| | |
|------------------------------|---|
| Safety Integrity Level (SIL) | 3 |
|------------------------------|---|

Safety data: EN IEC 62061

| | |
|------------------------------|---|
| Safety Integrity Level (SIL) | 3 |
|------------------------------|---|

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection | IP20 |
| Min. degree of protection of inst. location | IP54 |
| Ambient temperature (operation) | -20 °C ... 55 °C (observe derating) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Maximum altitude | ≤ 2000 m (Above sea level) |
| Max. permissible humidity (storage/transport) | 75 % (on average, 85% infrequently, non-condensing) |
| Max. permissible relative humidity (operation) | 75 % (on average, 85% infrequently, non-condensing) |
| Shock | 15g |
| Vibration (operation) | 10 Hz ... 150 Hz, 2g |

Standards and regulations

Air clearances and creepage distances between the power circuits

| | |
|-----------------------|----------------|
| Standards/regulations | DIN EN 60947-1 |
|-----------------------|----------------|

Mounting

| | |
|-----------------------|------------------------|
| Mounting type | DIN rail mounting |
| Assembly instructions | See derating curve |
| Mounting position | vertical or horizontal |

PSR-SCP- 24UC/ESM4/3X1/1X2/B - Safety relays



2963776

<https://www.phoenixcontact.com/us/products/2963776>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27371819 |
| ECLASS-13.0 | 27371819 |
| ECLASS-12.0 | 27371819 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001449 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39122205 |
|-------------|----------|

PSR-SCP- 24UC/ESM4/3X1/1X2/B - Safety relays



2963776

<https://www.phoenixcontact.com/us/products/2963776>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com