

2980283

https://www.phoenixcontact.com/us/products/2980283

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Passive feed-through bridge; can be plugged in instead of a relay or a solid-state relay, bridges terminal points A1 and 14

Commercial data

Item number	2980283
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	C461
Product key	CK6248
Catalog page	Page 426 (C-5-2019)
GTIN	4017918729981
Weight per piece (including packing)	2.975 g
Weight per piece (excluding packing)	2.9 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/2980283



Technical data

Product properties

	Product type	Bridge
Ele	ectrical properties	
	Nominal voltage U _N	60 V AC/DC
	Current (per branch)	≤1A

Dimensions

Item dimensions

Width	4.95 mm
Height	28 mm
Depth	18.4 mm

Material specifications

Color	black (RAL 9005)
00.0.	2.40tt (1.2.12.0000)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 60 °C
Ambient temperature (storage/transport)	-40 °C 85 °C

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
E	EN 60068-2-60

Mounting

Mounting position any



2980283

https://www.phoenixcontact.com/us/products/2980283

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27371692	
ECLASS-12.0	27371692	
ECLASS-13.0	27371692	
ETIM		
ETIM 9.0	EC002586	
UNSPSC		

39122300



https://www.phoenixcontact.com/us/products/2980283



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com