

https://www.phoenixcontact.com/us/products/3025163



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Shield connection clamp, for shield on busbars, contact resistance < 1 m Ω

Your advantages

- · Easy handling
- · Spring-loaded, large-surface pressure plate
- · Suitable for direct and busbar mounting
- Knurled screw
- As components, it is not possible to certify shield connections in accordance with the requirements of the directive and standards for electrical
 equipment in potentially explosive areas. As such, shield connection clamps can be used in the Ex area even without an appropriate approval or
 marking.

Commercial data

Item number	3025163
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE75
Product key	BE7512
Catalog page	Page 568 (C-3-2019)
GTIN	4017918130299
Weight per piece (including packing)	15.14 g
Weight per piece (excluding packing)	15.07 g
Customs tariff number	85369010
Country of origin	DE



https://www.phoenixcontact.com/us/products/3025163



Technical data

Product properties

Product type	Shield connection clamp
Pitch	12 mm
Number of connections	1
Number of rows	1

Electrical properties

Maximum power dissipation for nominal condition	0 W
Contact resistance	< 0.001 Ω

Connection data

Grounding foot	Yes
Screw thread	M4
Tightening torque	0.6 0.6 Nm
Connection in acc. with standard	IEC / EN

Dimensions

Dimensional drawing	19.5. (8) 12 12 12 13 13 13 13 13 13 13 13 13 13 13 13 13
Width	12 mm
Height	19.5 mm
Depth	48.7 mm
Pitch	12 mm
External dimensions	
Outside diameter	3 mm 8 mm

Material specifications

Color	silver
Material	Steel

Cable/line

External cable diameter	3 mm 8 mm
External cable diameter	3 11111 3 11111

Standards and regulations

Connection in acc. with standard	IEC / EN

Mounting

Mounting type	Neutral busbar
Mounting type	Neutral busbar



https://www.phoenixcontact.com/us/products/3025163



Classifications

ECLASS

	ECLASS-11.0	27141150	
	ECLASS-12.0	27141150	
	ECLASS-13.0	27250309	
ETIM			
	ETIM 9.0	EC002020	
UNSPSC			
	UNSPSC 21.0	39121400	



https://www.phoenixcontact.com/us/products/3025163



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com