

# SK 20 - Shield connection clamp

3025189

<https://www.phoenixcontact.com/us/products/3025189>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Shield connection clamp, for shield on busbars, contact resistance < 1 mΩ



## Your advantages

- Easy handling
- Spring-loaded, large-surface pressure plate
- Suitable for direct and busbar mounting
- Knurled screw
- As components, it is not possible to certify shield connections in accordance with the requirements of the directive and standards for electrical equipment in potentially explosive areas. As such, shield connection clamps can be used in the Ex area even without an appropriate approval or marking.

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3025189             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BE75                |
| Product key                          | BE7512              |
| Catalog page                         | Page 568 (C-3-2019) |
| GTIN                                 | 4017918130312       |
| Weight per piece (including packing) | 28.8 g              |
| Weight per piece (excluding packing) | 28 g                |
| Customs tariff number                | 85369010            |
| Country of origin                    | DE                  |

# SK 20 - Shield connection clamp

3025189

<https://www.phoenixcontact.com/us/products/3025189>

## Technical data

### Product properties

|                       |                         |
|-----------------------|-------------------------|
| Product type          | Shield connection clamp |
| Pitch                 | 24 mm                   |
| Number of connections | 1                       |
| Number of rows        | 1                       |


### Electrical properties

|   |                  |
|---|------------------|
| Maximum power dissipation for nominal condition | 0 W              |
| Contact resistance                              | < 0.001 $\Omega$ |

### Connection data

|                   |                |
|-------------------|----------------|
| Grounding foot    | Yes            |
| Screw thread      | M4             |
| Tightening torque | 0.8 ... 0.8 Nm |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 24 mm  |
| Height              | 19.5 mm  |
| Depth               | 75 mm  |
| Pitch               | 24 mm  |

### External dimensions

|                  |                |
|------------------|----------------|
| Outside diameter | 5 mm ... 20 mm |
|------------------|----------------|

### Material specifications

|          |        |
|----------|--------|
| Color    | silver |
| Material | Steel  |

### Cable/line

|                         |                |
|-------------------------|----------------|
| External cable diameter | 5 mm ... 20 mm |
|-------------------------|----------------|

### Mechanical properties

#### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

### Mounting

|               |                |
|---------------|----------------|
| Mounting type | Neutral busbar |
|---------------|----------------|

# SK 20 - Shield connection clamp



3025189

<https://www.phoenixcontact.com/us/products/3025189>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141150 |
| ECLASS-12.0 | 27141150 |
| ECLASS-13.0 | 27250309 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002020 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SK 20 - Shield connection clamp



3025189

<https://www.phoenixcontact.com/us/products/3025189>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)