## FBS 1/2/4/5-5 - Plug-in bridge

3030370

https://www.phoenixcontact.com/us/products/3030370

**PHŒNIX** CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 5.2 mm, number of positions: 5, pin assignment: 1, 2, 4, 5, color: red

### Commercial data

| Item number                          | 3030370       |
|--------------------------------------|---------------|
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE29          |
| Product key                          | BE2Z2X        |
| GTIN                                 | 4046356706988 |
| Weight per piece (including packing) | 3.85 g        |
| Weight per piece (excluding packing) | 3.85 g        |
| Customs tariff number                | 85366990      |
| Country of origin                    | PL            |

# FBS 1/2/4/5-5 - Plug-in bridge

3030370

https://www.phoenixcontact.com/us/products/3030370



### Technical data

| Product properties                     |  |  |  |
|--|--|--|--|
| Product type                           | Jumper   |  |  |
| Number of positions                    | 5  |  |  |
| Pitch                                  | 5.2 mm   |  |  |
| Electrical properties                  |  |  |  |
| Maximum load current                   | 24 A (The current values for the jumpers can deviate when used<br>in different modular terminal blocks. The precise values can be<br>found in the accessories data for the respective modular terminal<br>blocks.) |  |  |
| Connection data                        |  |  |  |
| Maximum load current                   | 24 A (The current values for the jumpers can deviate when used<br>in different modular terminal blocks. The precise values can be<br>found in the accessories data for the respective modular terminal<br>blocks.) |  |  |
| Dimensions                             |  |  |  |
| Pitch                                  | 5.2 mm   |  |  |
| Material specifications                |  |  |  |
| Color                                  | red  |  |  |
| Material                               | Copper   |  |  |
| Flammability rating according to UL 94 | V0   |  |  |
| Insulating material                    | PA   |  |  |
| Mechanical properties                  |  |  |  |
| Technical data                         |  |  |  |
| Pin assignment                         | 1, 2, 4, 5   |  |  |
| Mounting                               |  |  |  |
| Mounting type                          | Plug-in mounting   |  |  |
|  |  |  |  |

# FBS 1/2/4/5-5 - Plug-in bridge

3030370

https://www.phoenixcontact.com/us/products/3030370



## Classifications

#### ECLASS

| ECLASS-11.0 | 27141140 |
|-------------|----------|
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

#### ETIM

|        | ETIM 9.0    | EC000489 |  |
|--------|-------------|----------|--|
| UNSPSC |             |          |  |
|        | UNSPSC 21.0 | 39121400 |  |



3030370 https://www.phoenixcontact.com/us/products/3030370



### Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com