3036932

https://www.phoenixcontact.com/us/products/3036932

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Commercial data

| Item number | 3036932 |
|--------------------------------------|---------------------|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales key | BE29 |
| Product key | BE2Z2X |
| Catalog page | Page 403 (C-1-2019) |
| GTIN | 4017918930264 |
| Weight per piece (including packing) | 1.858 g |
| Weight per piece (excluding packing) | 1.858 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

3036932

https://www.phoenixcontact.com/us/products/3036932



Technical data

Product properties

| | Product type | Jumper |
|-----|----------------------|--|
| | Number of positions | 2 |
| | Pitch | 6.2 mm |
| Ele | ectrical properties | |
| | Maximum load current | 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
| Сс | onnection data | |
| | Maximum load current | 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

Dimensions

| Width | 10.7 mm |
|--------|---------|
| Height | 23 mm |
| Depth | 23 mm |
| Pitch | 6.2 mm |

Material specifications

| Color | blue |
|--|--------|
| Material | Copper |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |

Environmental and real-life conditions

| Ambient temperature (operation) | -60 °C 105 °C |
|--|---|
| Ambient temperature (storage/transport) | -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C 70 °C |
| Ambient temperature (actuation) | -5 °C 70 °C |
| Permissible humidity (storage/transport) | 30 % 70 % |

Mounting

| Hounting type | Mounting type Plu | ug-in mounting |
|---------------|-------------------|----------------|
|---------------|-------------------|----------------|

3036932

https://www.phoenixcontact.com/us/products/3036932



Classifications

ECLASS

| ECLASS-11.0 | 27141140 |
|-------------|----------|
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

ETIM

| | ETIM 9.0 | EC000489 |
|--------|-------------|----------|
| UNSPSC | | |
| | UNSPSC 21.0 | 39121400 |

3036932

https://www.phoenixcontact.com/us/products/3036932



Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com