

https://www.phoenixcontact.com/us/products/3038969



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 5.2 mm, number of positions: 2, color: gray

## Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

#### Commercial data

Item number	3038969
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE29
Product key	BE2Z2X
Catalog page	Page 403 (C-1-2019)
GTIN	4017918888299
Weight per piece (including packing)	1.701 g
Weight per piece (excluding packing)	1.685 g
Customs tariff number	85366990
Country of origin	DE



https://www.phoenixcontact.com/us/products/3038969



## Technical data

### Product properties

Product type	Jumper
Number of positions	2
Pitch	5.2 mm

## Electrical properties

Maximum load current	24 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

#### Connection data

Maximum load current	24 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

#### **Dimensions**

Pitch	5.2 mm

### Material specifications

Color	gray
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

#### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

### Mounting

Mounting type	Plug-in mounting	
---------------	------------------	--



https://www.phoenixcontact.com/us/products/3038969



# Classifications

UNSPSC 21.0

#### **ECLASS**

	ECLASS-11.0	27141140
	ECLASS-12.0	27141140
	ECLASS-13.0	27250303
ETIM		
	ETIM 9.0	EC000489
UNS	SPSC	

39121400



https://www.phoenixcontact.com/us/products/3038969



# Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com