

https://www.phoenixcontact.com/us/products/3040631



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Latching, can only be released using a screwdriver, width: 9 mm, height: 23.2 mm, number of positions: 2, color: orange

Commercial data

Item number	3040631
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE02
Product key	BE214Z
Catalog page	Page 363 (C-1-2019)
GTIN	4046356787765
Weight per piece (including packing)	0.602 g
Weight per piece (excluding packing)	0.584 g
Customs tariff number	39269097
Country of origin	PL



https://www.phoenixcontact.com/us/products/3040631



Technical data

Product properties

Product type	Mounting material
Number of positions	2

Dimensions

Width	9 mm
Height	23.2 mm

Material specifications

Color	orange
Material	PA-GF
Flammability rating according to UL 94	V2

Environmental and real-life conditions

Ambient conditions

, and other desired to the second sec	
Ambient temperature (operation)	-60 °C 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %



https://www.phoenixcontact.com/us/products/3040631



Classifications

ECLASS

	ECLASS-11.0	27141190
	ECLASS-12.0	27141190
	ECLASS-13.0	27141190
ET	IM	

EC002848

UNSPSC

ETIM 9.0

UNSPSC 21.0	39121400
-------------	----------

3040631

https://www.phoenixcontact.com/us/products/3040631



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com