

SSL 2,5 - Panel feed-through

3043815

<https://www.phoenixcontact.com/us/products/3043815>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Panel feed-through, width: 5.2 mm, color: gray



Your advantages

- Can be used for a plate thickness of 0.8 mm to 3 mm

Commercial data

Item number	3043815
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE02
Product key	BE214Z
Catalog page	Page 296 (C-1-2019)
GTIN	4017918936235
Weight per piece (including packing)	1.913 g
Weight per piece (excluding packing)	1.823 g
Customs tariff number	85389099
Country of origin	PL

SSL 2,5 - Panel feed-through

3043815

<https://www.phoenixcontact.com/us/products/3043815>

Technical data

Product properties

Product type	Mounting material
--------------	-------------------


Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Rated surge voltage	8.00 kV
---------------------	---------

Dimensions

Dimensional drawing	
Width	5.2 mm
Plate thickness	0.8 mm ... 3 mm

Installation dimensions

Length of the assembly cutout	16.6 mm
-------------------------------	---------

Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI)
---------------------------------	---

SSL 2,5 - Panel feed-through



3043815

<https://www.phoenixcontact.com/us/products/3043815>

	Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Plate thickness	0.8 mm ... 3 mm
-----------------	-----------------

SSL 2,5 - Panel feed-through



3043815

<https://www.phoenixcontact.com/us/products/3043815>

Classifications

ECLASS

ECLASS-11.0	27141190
ECLASS-12.0	27141190
ECLASS-13.0	27141190

ETIM

ETIM 9.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SSL 2,5 - Panel feed-through



3043815

<https://www.phoenixcontact.com/us/products/3043815>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com