

RB UT 16-ST(2,5/4) - Reducing bridge



3047099

<https://www.phoenixcontact.com/us/products/3047099>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Reducing bridge, pitch: 11 mm, number of positions: 2, length: 41 mm, color: red



Commercial data

Item number	3047099
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE19
Product key	BE1Z2X
Catalog page	Page 28 (C-3-2013)
GTIN	4046356055871
Weight per piece (including packing)	5.06 g
Weight per piece (excluding packing)	5.04 g
Customs tariff number	85366990
Country of origin	PL

RB UT 16-ST(2,5/4) - Reducing bridge



3047099

<https://www.phoenixcontact.com/us/products/3047099>

Technical data

Product properties

Product type	Reducing bridge
Number of positions	2
Pitch	11 mm

Dimensions

Width	18.1 mm
Height	40.9 mm
Depth	3 mm
Length	40.9 mm
Pitch	11 mm

Material specifications

Color	red
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C ()
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	Plug-in mounting
---------------	------------------

RB UT 16-ST(2,5/4) - Reducing bridge



3047099

<https://www.phoenixcontact.com/us/products/3047099>

Classifications

ECLASS

ECLASS-11.0	27141140
ECLASS-12.0	27141140
ECLASS-13.0	27250303

ETIM

ETIM 9.0	EC000489
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RB UT 16-ST(2,5/4) - Reducing bridge



3047099

<https://www.phoenixcontact.com/us/products/3047099>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com