

# UT 2,5-TWIN/1P-F - Screw flange

3061172

<https://www.phoenixcontact.com/us/products/3061172>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks

## Your advantages

- Same shape and pitch as the basic terminal blocks

## Commercial data

Item number	3061172
Packing unit	50 pc
Minimum order quantity	1 pc
Product key	BE114Z
Catalog page	Page 373 (C-1-2019)
GTIN	4046356366175
Weight per piece (including packing)	5.906 g
Weight per piece (excluding packing)	5.906 g
Country of origin	PL

# UT 2,5-TWIN/1P-F - Screw flange



3061172

<https://www.phoenixcontact.com/us/products/3061172>

## Technical data

### Product properties

Product type	Flange
Number of connections	0
Number of rows	1

### Connection data

Screw thread	M2,5
Tightening torque	0.4 ... 0.5 Nm

### Dimensions

Width	5.2 mm
End cover width	2.2 mm
Height	55.6 mm
Depth	46.9 mm
Depth on NS 35/7,5	47.5 mm
Depth on NS 35/15	55 mm

### Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

# UT 2,5-TWIN/1P-F - Screw flange

3061172

<https://www.phoenixcontact.com/us/products/3061172>



## Mounting

Mounting type	NS 35/7,5
	NS 35/15

# UT 2,5-TWIN/1P-F - Screw flange



3061172

<https://www.phoenixcontact.com/us/products/3061172>

## Classifications

### ECLASS

ECLASS-11.0	27141135
ECLASS-12.0	27141135
ECLASS-13.0	27250302

### ETIM

ETIM 9.0	EC001041
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# UT 2,5-TWIN/1P-F - Screw flange



3061172

<https://www.phoenixcontact.com/us/products/3061172>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)