

# FBP-2/12 - Blind plug

3069883

<https://www.phoenixcontact.com/us/products/3069883>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Blind plug, pitch: 8.2 mm, width: 130.8 mm, height: 72.9 mm, number of positions: 12, color: gray, mounting type: Insertion in base strip

## Your advantages

- Cost-effective, thanks to the tailored, modular design and use of standardized CLIPLINE complete accessories
- Blind plug for FAME..., used as a protective cover for the test block when the test plug is removed

## Commercial data

Item number	3069883
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	BE6112
Catalog page	Page 626 (C-1-2019)
GTIN	4046356962452
Weight per piece (including packing)	130.3 g
Weight per piece (excluding packing)	130.3 g
Customs tariff number	85389099
Country of origin	US

# FBP-2/12 - Blind plug



3069883

<https://www.phoenixcontact.com/us/products/3069883>

## Technical data

### Product properties

Product type	Blind plug
Number of positions	12
Pitch	8.2 mm

### Insulation characteristics

Overvoltage category	III
----------------------	-----

### Dimensions

Width	130.8 mm
Height	72.9 mm
Pitch	8.2 mm

### Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

### Mounting

# FBP-2/12 - Blind plug

3069883

<https://www.phoenixcontact.com/us/products/3069883>



Mounting type	Insertion in base strip
---------------	-------------------------

# FBP-2/12 - Blind plug

3069883

<https://www.phoenixcontact.com/us/products/3069883>



## Classifications

### ECLASS

ECLASS-11.0	27141190
ECLASS-12.0	27141190
ECLASS-13.0	27141190

### ETIM

ETIM 9.0	EC002848
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# FBP-2/12 - Blind plug

3069883

<https://www.phoenixcontact.com/us/products/3069883>



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)